

TWISTLOCK

F1-1L Rotation Twistlock

Specification: Min.B.L.Tension:500KN Min.B.L.Shear:420kN Finish:Hot dip galvanized.  
Material:High tensile stee Dimensions accordingto requirement.

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

|               |                                                                      |
|---------------|----------------------------------------------------------------------|
| Category      | Twistlock                                                            |
| Standard      | DIN                                                                  |
| Material      | Material:High tensile stee<br>Dimensions accordingto<br>requirement. |
| Weight / Size | Material:High tensile stee<br>Dimensions accordingto<br>requirement. |
| Certificate   | ABS, LR, BV, DNVGL, NK, KR,<br>IRS, RMRS, CCS                        |

We can supply according to your requirement,  
drawings, class certificate needs, and delivery  
schedule.

Technical Specifications

|               |                                                                      |             |                                                                      |
|---------------|----------------------------------------------------------------------|-------------|----------------------------------------------------------------------|
| Category      | Twistlock                                                            | Model / SKU | F1-1L-Rotation-Twistlock                                             |
| Standard      | DIN                                                                  | Material    | Material:High tensile stee<br>Dimensions accordingto<br>requirement. |
| Weight / Size | Material:High tensile stee<br>Dimensions accordingto<br>requirement. | Surface     | Hot dip galvanized                                                   |
| Certificate   | ABS, LR, BV, DNVGL, NK, KR,<br>IRS, RMRS, CCS                        | Warranty    | 12 Months unless specified<br>otherwise                              |
| Origin        | China                                                                |             |                                                                      |

Specification:

Min.B.L.Tension:500KN

Min.B.L.Shear:420kN

Finish:Hot dip galvanized.

Material:High tensile stee

Dimensions accordingto requirement.