

Twistlock

F7B-L Rotation Twistlock

Specification: Min.B.L.Tension:500KN Min.B.L.Shear:420kN Finish:Hot dip galvanized.
Material:High tensile stee Dimensions accordingto requirement.

ISO9001 Supplier

Class Certificate

Export Supply




F7B-L

jinbomarine.com



F4-L



F2-L

Key Highlights

Category	Twistlock
Standard	DIN
Material	Material:High tensile stee Dimensions accordingto requirement.
Weight / Size	Material:High tensile stee Dimensions accordingto requirement.
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement,
drawings, class certificate needs, and delivery
schedule.

Technical Specifications

Category	Twistlock	Model / SKU	F7B-L-Rotation-Twistlock
Standard	DIN	Material	Material:High tensile stee Dimensions accordingto requirement.
Weight / Size	Material:High tensile stee Dimensions accordingto requirement.	Surface	Hot dip galvanized
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

Specification:

Min.B.L.Tension:500KN

Min.B.L.Shear:420kN

Finish: Hot dip galvanized.

Material: High tensile steel

Dimensions according to requirement.

