

MARINE FLUORESCENT LIGHTS

Fluorescent Pendant Light JCY25-2P

Used to illumination of water dripping, water spattering, water coagulating place in ships such as oven cabin, dry cabin tunnel, pipeline and weather deck, environment temperature is -20°C~+55°C. Standards: Confirm t...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Fluorescent Lights
Standard	EN
Material	Steel Plate, PC Material and Seal Structure
Weight / Size	Type JCY25-2P JCY25-2PE Voltage 110V/60Hz, 220V/50Hz, 220V/60Hz Power Fa...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Fluorescent Lights	Model / SKU	Fluorescent-Pendant-Light-JCY25-2P
Standard	EN	Material	Steel Plate, PC Material and Seal Structure
Weight / Size	Type JCY25-2P JCY25-2PE Voltage 110V/60Hz, 220V/50Hz, 220V/60Hz Power Factor >0.85 Lamp Holder G13 Cable Diameter Dia14mm-16mm Protection Class IP56 Power 2x20W 2x20W Weight 4.55kg 4.55kg Material Engineering Plastic	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

- China Fluorescent Pendant Light JCY25-2P:
- Standards:
- Main Specification:

China Fluorescent Pendant Light JCY25-2P:



Used to illumination of water dripping, water spattering, water coagulating place in ships such as oven cabin, dry cabin tunnel, pipeline and weather deck, environment temperature is -20℃~+55℃.

Standards:

Confirm to IEC600092-306-2009 and GRADE ENTRY NORMS FOR STEEL SHIPS.

Our product approved by the CCS(China Classification Society)

Main Specification:

Type	JCY25-2P	JCY25-2PE
Voltage	110V/60Hz, 220V/50Hz, 220V/60Hz	
Power Factor	>0.85	
Lamp Holder	G13	
Cable Diameter	Dia14mm-16mm	
Protection Class	IP56	
Power	2x20W	2x20W
Weight	4.55kg	4.55kg
Material	Engineering Plastic	

