

MARINE FLUORESCENT LIGHTS


Fluorescent Pendant Light JCY26-1

Used to illumination the oven cabin, dry cabin tunnel, pipeline and weather deck, environment temperature is -20°C~+55°C.

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Fluorescent Lights
Standard	EN
Material	Steel Plate, PC Material and Seal Structure
Weight / Size	Type JCY26-1 JCY26-2 JCY26-2E JCY26-2EF Voltage 110V/60Hz, 220V/50Hz, 22...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.


Technical Specifications

Category	Marine Fluorescent Lights	Model / SKU	Fluorescent-Pendant-Light-JCY26-1
Standard	EN	Material	Steel Plate, PC Material and Seal Structure
Weight / Size	Type JCY26-1 JCY26-2 JCY26-2E JCY26-2EF Voltage 110V/60Hz, 220V/50Hz, 220V/60Hz Power Factor >0.85 Lamp Holder G13 Cable Diameter Dia14mm-16mm Protection Class IP56 Power 1x20W 1x20W 2X20W 2X20W Weight 7.2kg 7.2kg 7.2kg 7.2kg	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

- China Fluorescent Pendant Light JCY26-1:
- Standards:
- Main Specification:

China Fluorescent Pendant Light JCY26-1:



Used to illumination the oven cabin, dry cabin tunnel, pipeline and weather deck, environment temperature is -20℃~+55℃.

Standards:

Confirm to IEC600092-306-2009 and GRADE ENTRY NORMS FOR STEEL SHIPS.

Our product approved by the CCS(China Classification Society)

Main Specification:

Type	JCY26-1	JCY26-2	JCY26-2E	JCY26-2EF
Voltage	110V/60Hz, 220V/50Hz, 220V/60Hz			
Power Factor	>0.85			
Lamp Holder	G13			
Cable Diameter	Dia14mm-16mm			
Protection Class	IP56			
Power	1x20W	1x20W	2X20W	2X20W
Weight	7.2kg	7.2kg	7.2kg	7.2kg