

MANUAL OPERATED FIRE MONITOR

Foam And Water Fire Monitor PL24-64

Type: PL24-64A Flow Range: 24-64 L/S Adjustable (380-1000GPM) Working Pressure: 10 bar
Max Reach @ Max Flow: 65m (Water) and 60M (Foam) Range of motion: -45°~+90°Vert ,
360°Rot Max fog angle : 120° Material (body) : A...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Manual Operated Fire Monitor
Standard	EN
Material	-45°~+90°Vert , 360°Rot Max fog angle : 120° Material (body) : Aluminum Mat...
Weight / Size	-45°~+90°Vert , 360°Rot Max fog angle : 120° Material (body) : Aluminum Mat...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Manual Operated Fire Monitor	Model / SKU	Foam-And-Water-Fire-Monitor-PL24-64
Standard	EN	Material	-45°~+90°Vert , 360°Rot Max fog angle : 120° Material (body) : Aluminum Material (nozzle) : Aluminum, with stream sharper Material (Tiller) : 304 stainless steel with rubber handle Pump requirement for minimum performance : 24L/S@ 8 bar Pipe dimensions for installation:
Weight / Size	-45°~+90°Vert , 360°Rot Max fog angle : 120° Material (body) : Aluminum Material (nozzle) : Aluminum, with stream sharper Material (Tiller) : 304 stainless steel with rubber handle Pump requirement for minimum performance : 24L/S@ 8 bar Pipe dimensions for installation:	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

China Foam And Water Fire Monitor PL24-64:

Type: PL24-64A

Flow Range: 24-64 L/S Adjustable (380-1000GPM)

Working Pressure: 10 bar

Max Reach @ Max Flow: 65m (Water) and 60M (Foam)

Range of motion: -45°~+90°Vert , 360°Rot

Max fog angle : 120°

Material (body) : Aluminum

Material (nozzle) : Aluminum, with stream sharper

Material (Tiller) : 304 stainless steel with rubber handle

Pump requirement for minimum performance : 24L/S@ 8 bar

Pipe dimensions for installation: 4 Inch

Monitor Inlet: DN100 flange

Monitor Outlet : 2.5 inch (65mm)

Paint: Fire Red

