SEWAGE PUMP

FS Series Marine updraft Subersible Pump

ISO9001 Supplier

Class Certificate

Export Supply

FS series is suitable for conveying temperature not exceed 40 ℃, sediment concentration or insoluble in water volume ratio less than 0.1% of solid particles, particle size is not more than 0.2 mm of water or weak corros...



Key Highlights

Category	Sewage Pump
Standard	EN
Weight / Size	FS series is suitable for conveying temperature not exceed 40 ℃, sedimen...
Certificate	ABS,LR, BV, GL CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Sewage Pump	**Model / SKU**	FS-Series-Marine-updraft-Subersible-Pump
Standard	EN	**Weight / Size**	FS series is suitable for conveying temperature not exceed 40 ℃, sediment concentration or insoluble in water volume ratio less than 0.1% of solid particles, particle size is not more than 0.2 mm of water or weak corrosive liquid and water supply and drainage, etc.
Certificate	ABS,LR, BV, GL CCS	**Warranty**	12 Months unless specified otherwise
Origin	China		

CONTENTS
- China FS Series Marine updraft Subersible Pump:
- Main Specification

China FS Series Marine updraft Subersible Pump:



FS series is suitable for conveying temperature not exceed 40 ℃, sediment concentration or insoluble in water volume ratio less than 0.1% of solid particles, particle size is not more than 0.2 mm of water or weak corrosive liquid and water supply and drainage, etc.

Main Specification

Type	Capacity	Head	Power	Current	Caliber	Weight
	m3/h	m	kw	A	mm	kg
FS8.4-40-2.2	8.4	40	2.2	5.7	40	45
FS15-26-2.2	15	26	2.2	5.7	40	49
FS25-17-2.2	25	17	2.2	5.7	50	41
FS65-7-2.2	65	7	2.2	5.7	100	41
FS100-4.5-2.2	100	4.5	2.2	5.7	128	38
FS8.4-50-3	8.4	50	3	7.54	40	47
FS12.5-40-3	12.5	40	3	7.54	40	47
FS15-36-3	15	36	3	7.54	40	46
FS20-30-3	20	30	3	7.54	40	48
FS25-36-3	25	26	3	7.54	50	46
FS40-16-3	40	16	3	7.54	65	47
FS65-10-3	65	10	3	7.54	100	45
FS100-6-3	100	6	3	7.54	128	48
FS160-4-3	160	4	3	7.54	128	43
FS12.5-50-4	12.5	50	4	8.9	40	59
FS25-32-4	25	32	4	8.9	50	57

FS40-21-4	40	21	4	8.9	65	54
FS65-13-4	65	13	4	8.9	100	51
FS200-4-4	200	4	4	8.9	150	52
FS20-50-5.5	20	50	5.5	12	50	75
FS25-40-5.5	25	40	5.5	12	50	76
FS40-28-5.5	40	28	5.5	12	65	83
FS100-12-5.5	100	12	5.5	12	125	65
FS40-40-7.5	40	40	7.5	16.8	65	105
FS65-26-7.5	65	26	7.5	16.8	80	101
FS200-9-7.5	200	9	7.5	16.8	150	100