

SEWAGE PUMP

FX Seires Marine Downdraft Submersible Pump

FX Seires Marine downdraft Submersible Pump are used to transport the freshwater and other purpose the temperature is not higher than 40°C, solid granules is not more than 0.2mm. Impeller with against pine device, Mech...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Sewage Pump
Standard	EN
Material	Impeller with against pine device, Mechanical seal face material USES si...
Weight / Size	Main Specification Type Capacity Head Power Current Caliber Weight (m3/h...
Certificate	CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Sewage Pump	Model / SKU	FX-Seires-Marine-Dwndraft-Submersible-Pump
Standard	EN	Material	Impeller with against pine device, Mechanical seal face material USES silicon carbide - silicon carbide, durable, safe and reliable.
Weight / Size	Main Specification Type Capacity Head Power Current Caliber Weight (m3/h) (l/s) (m) (kW) (A) (mm) (kg) FX10-14-0.75 10 2.8 14 0.75 1.8 40 40 FX6-25-1.1 6 1.7 25 1.1 2.73 25 25 FX10-18-1.1 10 2.8 18 1.1 2.73 40 25 FX15-14-1.1 15 4.2 14 1.1 2.73 40 25 FX25-9- 1.1 25 6.9 9 1.1 2.73 50 25 FX40- 6-1.1 40 11.1 6 1.1 2.73 65 34 FX10-24-1.5 10 2.8 24 1.5 3.87 40 32 FX10-34-2.2 10 2.8 34 2.2 6 40 39 FX25-30-3 25 6.9 30 3 6.5 50 45 FX15-45-4 15 4.2 45 4 8.6 40 49 FX25-32-4 25 6.9 32 4 8.6 50 49 FX25-40-5.5 25 6.9 40 5.5 12 50 64	Certificate	CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS	■ China FX Seires Marine Dwndraft Submersible Pump:	■ Main Specification
----------	---	----------------------

China FX Seires Marine Dwndraft Submersible Pump:



FX Seires Marine downdraft Submersible Pump are used to transport the freshwater and other purpose the temperature is not higher than 40°C, solid granules is not more than 0.2mm. Impeller with against pine device, Mechanical seal face material USES silicon carbide - silicon carbide, durable, safe and reliable.

Main Specification

Type	Capacity		Head	Power	Current	Caliber	Weight
	(m3/h)	(l/s)	(m)	(kW)	(A)	(mm)	(kg)
FX10-14-0.75	10	2.8	14	0.75	1.8	40	40
FX6-25-1.1	6	1.7	25	1.1	2.73	25	25
FX10-18-1.1	10	2.8	18	1.1	2.73	40	25
FX15-14-1.1	15	4.2	14	1.1	2.73	40	25
FX25-9-1.1	25	6.9	9	1.1	2.73	50	25
FX40-6-1.1	40	11.1	6	1.1	2.73	65	34
FX10-24-1.5	10	2.8	24	1.5	3.87	40	32
FX10-34-2.2	10	2.8	34	2.2	6	40	39
FX25-30-3	25	6.9	30	3	6.5	50	45
FX15-45-4	15	4.2	45	4	8.6	40	49
FX25-32-4	25	6.9	32	4	8.6	50	49
FX25-40-5.5	25	6.9	40	5.5	12	50	64