

HIGH PRESSURE PUMP

FYB-225 with 4 Outlets Air Driven High Pressure Hydraulic Pump

ISO9001 Supplier

Class Certificate

Export Supply

FYB-225 Air Driven High Pressure Hydraulic Pump With four ways outlets: FYB-225 Air Driven High Pressure Hydraulic Pump is a new type of hydraulic stretching and pressing equipment. It transforms the lower air...



Key Highlights

Category	High Pressure Pump
Standard	DIN
Weight / Size	It can be widely used in large and medium-sized mechanical screw fasteni...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	High Pressure Pump	Model / SKU	FYB-225-with-4-Outlets-Air-Driven-High-Pressure-Hydraulic-Pump
Standard	DIN	Weight / Size	It can be widely used in large and medium-sized mechanical screw fastening, large transmission parts and keyless matching of structural parts in metallurgical mining, petrochemical industry, shipbuilding industry, locomotive and vehicle manufacturing industry.
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	■ China FYB-225 with 4 Outlets Air Driven High Pressure Hydraulic Pump:	■ FYB-225 Air Driven High Pressure Hydraulic Pump With four ways outlets:
	■ Spar parts kit:	

China FYB-225 with 4 Outlets Air Driven High Pressure Hydraulic Pump:

FYB-225 Air Driven High Pressure Hydraulic Pump With four ways outlets:

FYB-225 Air Driven High Pressure Hydraulic Pump is a new type of hydraulic stretching and pressing equipment. It transforms the lower air pressure into pressure oil and becomes an ideal power source.

FYB series hydraulic booster pump has the advantages of high output pressure, simple operation, safe and reliable, easy to carry and so on. It can be widely used in large and medium-sized mechanical screw fastening, large transmission parts and keyless matching of structural parts in metallurgical mining, petrochemical industry, shipbuilding industry, locomotive and vehicle manufacturing industry. It is an ideal tool for assembling and matching various large and medium-sized machines.

Model	FYB-225
Weight	28KG(net weight)
Size	430*370*415 mm
Output pressure	Maximum 225MPa (input air pressure 9bar)
Output port	4PCS
Pump working speed	About. 450 cydles per
	minute, input pressure 8bar
Tank capacity	4.5L
Air consumption	1.05 liters 1 minutes,input pressure 8bar
Maxi flow (At no pressure)	About 0.35 liters I mins,
	input pressure 8bar
Oil supply per circle	0.8 mliliter (0.049 cubic inches)

Spar parts kit:



2 meters High pressure pipe 4PCS

