

CONNECTORS

G2130 Bow Shackle

The bow shackle is common produce used in the offshore industry,this shackle can be used in temporary and permanent in the mooring system, finish is hot dip galvanized.

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Connectors
Standard	EN
Weight / Size	Nominal Size Working Load Dimensions Weight (in.) (tons) A B C D E F H L...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.	

Technical Specifications			
Category	Connectors	Model / SKU	G2130-Bow-Shackle
Standard	EN	Weight / Size	Nominal Size Working Load Dimensions Weight (in.) (tons) A B C D E F H L N (lbs.) 3/16 1/3 0.38 0.25 0.88 0.19 0.6 0.56 1.47 0.98 0.19 0.06 1/4 1/2 0.47 0.31 1.13 0.25 0.78 0.61 1.84 1.28 0.25 0.11 5/16 3/4 0.53 0.38 1.22 0.31 0.84 0.75 2.09 1.47 0.31 0.22 3/8 1 0.66 0.44 1.44 0.38 1.03 0.91 2.49 1.78 0.38 0.33 7/16 1 1/2 0.75 0.5 1.69 0.44 1.16 1.06 2.91 2.03 0.44 0.49 1/2 2 0.81 0.64 1.88 0.5 1.31 1.19 3.28 2.31 0.5 0.79 5/8 3 1/4 1.06 0.77 2.38 0.63 1.69 1.5 4.19 2.94 0.69 1.68 3/4 4 3/4 1.25 0.89 2.81 0.75 2 1.81 4.97 3.5 0.81 2.72 7/8 6 1/2 1.44 1.02 3.31 0.88 2.28 2.09 5.83 4.03 0.97 3.95 1 8 1/2 1.69 1.15 3.75 1 2.69 2.38 6.56 4.69 1.06 5.66 1 1/8 9 1/2 1.81 1.25 4.25 1.13 2.91 2.69 7.47 5.16 1.25 8.27 1 1/4 12 2.03 1.4 4.69 1.29 3.25 3 8.25 5.75 1.38 11.71 1 3/8 13 1/1 2.25 1.53 5.25 1.42 3.63 3.31 9.16 6.38 1.5 15.83 1 1/2 17 2.38 1.66 5.75 1.53 3.88 3.63 10 6.88 1.62 19 1 3/4 25 2.88 2.04 7 1.84 5 4.19 12.34 8.8 2.25 33.91 2 35 3.25 2.3 7.75 2.08 5.75 4.81 13.68 10.15 2.4 52.25 2.5 55 4.13 2.8 10.5 2.71 7.25 5.69 17.9 12.75 3.13 98.25 3 85 5 3.3 13 3.12 7.88 6.5 21.5 14.62 3.62 154 3.5 120 5.25 3.76 14.63 3.62 9 8 24.88 17.02 4.38 265 4 150 5.5 4.26 14.5 4 10 9 25.68 18 4.56 338
Surface	hot dip galvanized	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

- China G2130 Bow Shackle:

- Main Specification:

China G2130 Bow Shackle:



The bow shackle is common produce used in the offshore industry, this shackle can be used in temporary and permanent in the mooring system, finish is hot dip galvanized.

Main Specification:

Nominal Size	Working Load	Dimensions									Weight
(in.)	(tons)	A	B	C	D	E	F	H	L	N	(lbs.)
3/16	1/3	0.38	0.25	0.88	0.19	0.6	0.56	1.47	0.98	0.19	0.06
1/4	1/2	0.47	0.31	1.13	0.25	0.78	0.61	1.84	1.28	0.25	0.11
5/16	3/4	0.53	0.38	1.22	0.31	0.84	0.75	2.09	1.47	0.31	0.22
3/8	1	0.66	0.44	1.44	0.38	1.03	0.91	2.49	1.78	0.38	0.33
7/16	1 1/2	0.75	0.5	1.69	0.44	1.16	1.06	2.91	2.03	0.44	0.49
1/2	2	0.81	0.64	1.88	0.5	1.31	1.19	3.28	2.31	0.5	0.79
5/8	3 1/4	1.06	0.77	2.38	0.63	1.69	1.5	4.19	2.94	0.69	1.68
3/4	4 3/4	1.25	0.89	2.81	0.75	2	1.81	4.97	3.5	0.81	2.72
7/8	6 1/2	1.44	1.02	3.31	0.88	2.28	2.09	5.83	4.03	0.97	3.95
1	8 1/2	1.69	1.15	3.75	1	2.69	2.38	6.56	4.69	1.06	5.66
1 1/8	9 1/2	1.81	1.25	4.25	1.13	2.91	2.69	7.47	5.16	1.25	8.27
1 1/4	12	2.03	1.4	4.69	1.29	3.25	3	8.25	5.75	1.38	11.71
1 3/8	13 1/1	2.25	1.53	5.25	1.42	3.63	3.31	9.16	6.38	1.5	15.83
1 1/2	17	2.38	1.66	5.75	1.53	3.88	3.63	10	6.88	1.62	19
1 3/4	25	2.88	2.04	7	1.84	5	4.19	12.34	8.8	2.25	33.91
2	35	3.25	2.3	7.75	2.08	5.75	4.81	13.68	10.15	2.4	52.25
2.5	55	4.13	2.8	10.5	2.71	7.25	5.69	17.9	12.75	3.13	98.25
3	85	5	3.3	13	3.12	7.88	6.5	21.5	14.62	3.62	154

3.5	120	5.25	3.76	14.63	3.62	9	8	24.88	17.02	4.38	265
4	150	5.5	4.26	14.5	4	10	9	25.68	18	4.56	338

