

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

INDUSTRIAL CHAINS

G30 Galvanized Link Chain

G30 Galvanized Link Chain Material: Steel Diameter: 4mm to 26mm. Surface Finish: Electrocal Galvanized or Hot Dip Galvanized G30 Link Chain Dimension Nominal Size ...

- ISO9001 Supplier
- Class Certificate
- Export Supply



Key Highlights

Category	Industrial Chains
Standard	EN
Material	Steel
Weight / Size	Electrocal Galvanized or Hot Dip Galvanized G30 Link Chain Dimension Nom...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Industrial Chains	Model / SKU	G30-Galvanized-Link-Chain
Standard	EN	Material	Steel
Weight / Size	Electrocal Galvanized or Hot Dip Galvanized G30 Link Chain Dimension Nominal Size Working Load Proof Test Load Breaking Load Inside Length Inside Width MM IN KG LBS KN LBS KN LBS MM IN MM IN 4 5/32 180 400 3.8 800 7.2 1600 23.9 0.94 6.4 0.25 5.5 3/16 365 800 7.2 1500 14.4 3200 24.8 0.98 7.7 0.3 7 1/4 580 1300 11.6 2600 23.2 5200 31.5 1.24 9.8 0.38 8 5/16 860 1900 16.9 3800 33.8 7600 32.8 1.29 11.2 0.44 10 3/8 1200 2650 23.5 5300 47.2 10600 35 1.38 14 0.55 11.9 7/16 1680 3700 32.9 7400 65.8 14800 41.5 1.64 16.6 0.65 13 1/2 2030 4500 40 9000 80 18000 45.5 1.79 18.2 0.72 16 5/8 3130 6900 61.3 13800 122.8 27600 56 2.2 20 0.79 20 3/4 4800 10600 94.3 21200 188.6 42400 70 2.78 25 0.98 22 7/8 5810 12800 114.1 25600 228.1 51200 77 3.03 27.5 1.08 25 1 8140 17900 159.1 35800 318 71600 90.9 3.58 31.7 1.25	Surface	Galvanized
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	■ China G30 Galvanized Link Chain:	■ G30 Link Chain Dimension
-----------------	------------------------------------	----------------------------

China G30 Galvanized Link Chain:

G30 Galvanized Link Chain

Material: Steel

Diameter: 4mm to 26mm.

Surface Finish: Electrocal Galvanized or Hot Dip Galvanized

G30 Link Chain Dimension

Nominal Size		Working Load		Proof Test Load		Breaking Load		Inside Length		Inside Width	
MM	IN	KG	LBS	KN	LBS	KN	LBS	MM	IN	MM	IN
4	5/32	180	400	3.8	800	7.2	1600	23.9	0.94	6.4	0.25
5.5	3/16	365	800	7.2	1500	14.4	3200	24.8	0.98	7.7	0.3
7	1/4	580	1300	11.6	2600	23.2	5200	31.5	1.24	9.8	0.38
8	5/16	860	1900	16.9	3800	33.8	7600	32.8	1.29	11.2	0.44
10	3/8	1200	2650	23.5	5300	47.2	10600	35	1.38	14	0.55
11.9	7/16	1680	3700	32.9	7400	65.8	14800	41.5	1.64	16.6	0.65
13	1/2	2030	4500	40	9000	80	18000	45.5	1.79	18.2	0.72
16	5/8	3130	6900	61.3	13800	122.8	27600	56	2.2	20	0.79
20	3/4	4800	10600	94.3	21200	188.6	42400	70	2.78	25	0.98
22	7/8	5810	12800	114.1	25600	228.1	51200	77	3.03	27.5	1.08
25	1	8140	17900	159.1	35800	318	71600	90.9	3.58	31.7	1.25