MARINE ENGINE TELEGRAPH SYSTEM

GCWD-2 Fog Horn Control System

GCWD-2 Fog Horn Control System The fog whistle controller consists of an operation display panel (dual whistle, single whistle) and an input/output module. Features: 1, automatic fog whist...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Engine Telegraph System
Standard	EN
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Engine Telegraph System	**Model / SKU**	GCWD-2-Fog-Horn-Control-System
Standard	EN	**Certificate**	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	**Origin**	China

GCWD-2 Fog Horn Control System

The fog whistle controller consists of an operation display panel (dual whistle, single whistle) and an input/output module.



Features:

1, automatic fog whistle timing

One long and three short every 2 minutes;One long and two short every 2 minutes;One long and one short every 2 minutesEvery 2 minutes;

Three shorts per minute;

One short, one long and one short every 1 minute;2, manually whistle

Press the "Manual" button at the touch of a button,thetoghorn controller automatically switches to "Manual" andsends the signal at the "manual”rhythm.Press the“Stop”or“Manual" touch button, then press the left and right sidecontrol buttons (external) to control manually.

3,external control input

External manual button or universal alarm contact can beused.

4,control output

Passing fog light passive contact;

Passing the passive contact of the flute solenoid valve;Electrically heating the passive contact;

5, you can press the "dirnming" touch button to adjust thebrightness of the indicator light, with automatic power-offfunction.

Technical Parameters:

1,Power supply:AC220V主20%;2,Solenoid valve≤10OW;

3,The fog lamp power is≤10OW;

4, electric heating control terminal power≤200W;5, the ambient temperature:-10~ C~+50°cG,relativc humidity:≤RH95%6(+40“C,

7, It has good electromagnetic compatibility , and there arestrict anti-interference measures in the microcomputertechnology;

8,Ingress protection: IP22