

MARINE COMMUNICATION AND NAVIGATION EQUIPMENT

ISO9001 Supplier

Class Certificate

Export Supply

GPS Antenna

GPS Antenna Specification Frequency: 1575MHZ+/-10Mhz Gain:36dB SWR:<2.0
Impedance: 50 Ohm DC Voltage: 3V-5V Working Tempature: -40-84 degree C. Cable: 7.6M,
-3 Cable Po...



Key Highlights

Category	Marine Communication And Navigation Equipment
Standard	EN
Weight / Size	BNC-C-J5 Net Weight:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Communication And Navigation Equipment	Model / SKU	GPS-Antenna
Standard	EN	Weight / Size	BNC-C-J5 Net Weight:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

■ GPS Antenna Specification

■ AIS,VHF and other Antenna

GPS Antenna Specification

Frequency: 1575MHZ+/-10Mhz

Gain:36dB

SWR:<2.0

Impedance: 50 Ohm

DC Voltage: 3V-5V

Working Tempature: -40-84 degree C.

Cable: 7.6M, -3 Cable

Polarization: RHCP

Cable Connector: BNC-C-J5

Net Weight: 440g

AIS,VHF and other Antenna

► Marine antenna

 GPS Antenna Frequency: 1575MHz ±10MHz Gain: 36db SWR: <2.0 Impedance: 50 ohm DC voltage: 3V-5V Working temperature : -40-85℃ Cable: 7.6m, -3 cable Polarization: RHCP Cable connector : BNC-C-J5 or TNC-J5 Net weight: 440g	 AIS Antenna Frequency: 156-163MHz SWR: <1.3 Impedance: 50 ohm Materials: FRP Length: 128.5 cm	 VHF Antenna Frequency: 140-170MHz SWR: <1.5 Gain: 3dB Impedance: 50 ohm Materials: aluminum jacket Maximum power: <200W Length: 127 cm
 SSB Antenna(Radio Antenna) Frequency: 1-30MHz SWR: <1.5 Mainline: -5 black cable (12m) Feeder line: -3 white cable (15m) Net weight: 3.3kg	 747 Antenna(Intercom) Frequency: 27-39MHz; Bandwidth: 5MHz	 90C Antenna(Intercom) Frequency: 27-39MHz; Single row
 90C Antenna(Intercom) Frequency: 27-39MHz; Double row	 Square/round shaped Antenna(Intercom) Frequency: 27-39MHz; Bandwidth: 5MHz	