

NAVIGATION BUOY

GRP Tower

Specification Diameter: 1m Temperature Range: -40°C to 55°C Wind Velocity:45m/s Life: Over 10yeras Weight: 900kgs(height of 10M) Gencral Thickness:10mm Thickness of Joining Porti...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Navigation Buoy
Standard	EN
Weight / Size	Over 10yeras Weight:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Navigation Buoy	Model / SKU	GRP-Tower
Standard	EN	Weight / Size	Over 10yeras Weight:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

China GRP Tower:

Specification

Diameter: 1m

Temperature Range: -40°C to 55°C

Wind Velocity:45m/s

Life: Over 10yeras

Weight: 900kgs(height of 10M)

Gencral Thickness:10mm

Thickness of Joining Portion: 12mm

Thickness of GRP Foundation:<12mm

Height of GRP Tower : 5.5m to 10m.

Mounting Requirement: Concrete foundation fitted with 24 stud bolts of 16mm, PCD 1680mm

Location; Coast and inland river.