

ELECTRIC HEATER

HA Series Bearing Heater

HA Series Bearing Heater &nbsp; &nbsp; &nbsp; HA series bearing heaters are mainly used to heat various types of metal parts such as bearings,bushings, shaft sleeves,diameter rings, pulleys,shrink rings, connectors, etc.,and...

ISO9001 Supplier

Class Certificate

Export Supply



jinbomarine.com

Key Highlights

|               |                                                                             |
|---------------|-----------------------------------------------------------------------------|
| Category      | Electric Heater                                                             |
| Standard      | EN                                                                          |
| Weight / Size | heating temperature 300 °C 300°C 300°C 300 °C 300°C Heating theworkpiece... |
| Certificate   | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS                                  |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

|             |                                            |               |                                                                                                                                                                                                                                                                                                                                                                |
|-------------|--------------------------------------------|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Category    | Electric Heater                            | Model / SKU   | HA-Series-Bearing-Heater                                                                                                                                                                                                                                                                                                                                       |
| Standard    | EN                                         | Weight / Size | heating temperature 300 °C 300°C 300°C 300°C 300 °C 300°C Heating theworkpiece Internal diameter Φ30-70mm Φ30-100mm Φ60-200mm Φ60-250mm Φ80-360mm Φ180-400mm Outer diameter >Φ250mm >Φ360mm >Φ440mm >Φ480mm >Φ510mm >Φ530mm Width 110mm 115mm 140mm 180mm 200mm 220mm Weight 45kg 55kg 85kg 120kg 135kg 150kg Demagnetization effect Residual magnetism≤ 1.0mT |
| Certificate | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS | Warranty      | 12 Months unless specified otherwise                                                                                                                                                                                                                                                                                                                           |
| Origin      | China                                      |               |                                                                                                                                                                                                                                                                                                                                                                |

## China HA Series Bearing Heater:

### HA Series Bearing Heater

HA series bearing heaters are mainly used to heat various types of metal parts such as bearings,bushings, shaft sleeves,diameter rings, pulleys,shrink rings, connectors, etc.,and expand them by heating to meet the needs of interference assembly.

| Model                       |                   | HA-1                                              | HA-2      | HA-3      | HA-4      | HA-5      | HA-6       |
|-----------------------------|-------------------|---------------------------------------------------|-----------|-----------|-----------|-----------|------------|
| Rated power                 |                   | 2.2KVA                                            | 3.3KVA    | 5.5KVA    | 9KVA      | 12KVA     | 14KVA      |
| Rated voltage               |                   | 220V                                              | 220V      | 380V      | 380V      | 380V      | 380V       |
| Rated current               |                   | 10A                                               | 12A       | 15A       | 20A       | 30A       | 135A       |
| Control method              |                   | Manual control, temperature control, time control |           |           |           |           |            |
| Magnetic probe              |                   | Have                                              | Have      | Have      | Have      | Have      | Have       |
| Automatic demagnetization   |                   | Automatic                                         | Automatic | Automatic | Automatic | Automatic | Automatic  |
| Time digital display        |                   | Have                                              | Have      | Have      | Have      | Have      | Have       |
| Temperature digital display |                   | Have                                              | Have      | Have      | Have      | Have      | Have       |
| Max. heating temperature    |                   | 300 °C                                            | 300°C     | 300°C     | 300°C     | 300 °C    | 300°C      |
| Heating the workpiece       | Internal diameter | Φ30-70mm                                          | Φ30-100mm | Φ60-200mm | Φ60-250mm | Φ80-360mm | Φ180-400mm |
|                             | Outer diameter    | >Φ250mm                                           | >Φ360mm   | >Φ440mm   | >Φ480mm   | >Φ510mm   | >Φ530mm    |
|                             | Width             | 110mm                                             | 115mm     | 140mm     | 180mm     | 200mm     | 220mm      |
| Weight                      |                   | 45kg                                              | 55kg      | 85kg      | 120kg     | 135kg     | 150kg      |
| Demagnetization effect      |                   | Residual magnetism≤ 1.0mT                         |           |           |           |           |            |