

HAMMER UNION

Hammer Union 3" Figure 1003 Thread

Type 1003 union rated pressure 10000 PSI NSCWP (7500 psi NSCWP, in 4, 5 in), recommended for applied to air, water, gas, oil, mud or air use occasion. Union has a spherical seat, which can provide the off-center ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Hammer Union
Standard	EN
Material	In addition to the steel on steel cooperation, nitrile rubber type O - r...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.	

Technical Specifications

Category	Hammer Union	Model / SKU	Hammer-Union-3-Figure-1003-Thread
Standard	EN	Material	In addition to the steel on steel cooperation, nitrile rubber type O - ring to ensure the position in any deflection connection tightness.
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

China Hammer Union 3" Figure 1003 Thread:

Type 1003 union rated pressure 10000 PSI NSCWP (7500 psi NSCWP, in 4, 5 in), recommended for applied to air, water, gas, oil, mud or air use occasion. Union has a spherical seat, which can provide the off-center 71/2 degree deflection or Angle adjustment, the total deflection capacity is 15 degrees. In addition to the steel on steel cooperation, nitrile rubber type O - ring to ensure the position in any deflection connection tightness.