

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

HAMMER UNION

Hammer Union 3" Figure 602 Thread

Type 602 union rated pressure 6000 PSI NSCWP, test pressure 9000 PSI. Recommended for cementing, fracturing, acidizing, test and blocking and kill line and also can be used for pressure sealing connection, using butt ...

- ISO9001 Supplier
- Class Certificate
- Export Supply



Key Highlights

Category	Hammer Union
Standard	DIN
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Hammer Union	Model / SKU	Hammer-Union-3-Figure-602-Thread
Standard	DIN	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

China Hammer Union 3" Figure 602 Thread:

Type 602 union rated pressure 6000 PSI NSCWP, test pressure 9000 PSI. Recommended for cementing, fracturing, acidizing, test and blocking and kill line and also can be used for pressure sealing connection, using butt welding Sch XXH. Equipped with a replaceable elastic nitrile rubber sealing ring, strong wall thickness design used in high pressure system