

MARINE NAVIGATION SIGNAL LIGHT

Head Light

Used as lamp signal for navigation.

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Navigation Signal Light
Standard	GB
Material	Confirm to the international regulation for preventing collision at sea,...
Weight / Size	Type CXH5-1 CXH5-1A CXH5-1B CXH5-2 CXH-2A CXH-2B CXH5-3 Visibility 3n.m ...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Marine Navigation Signal Light	Model / SKU	Head-Light
Standard	GB	Material	Confirm to the international regulation for preventing collision at sea, 1972 and grade entry norms for steel ships.
Weight / Size	Type CXH5-1 CXH5-1A CXH5-1B CXH5-2 CXH-2A CXH-2B CXH5-3 Visibility 3n.m 3n.m 3n.m 2n.m 2n.m 2n.m 2n.m Level arc 360o 360o 360o 360o 360o 360o Material Aluminum Plastic Stainless Steel Aluminum Plastic Stainless Steel Plastic Weight 0.9kgs 0.73kgs 1.73kgs 0.4kgs 0.5kgs 1.25kgs 0.3kgs Voltage 24V,110V,220V 24V 24V,12V Power 60W 30W 15W Color White, Red, Green, Yellow,Blue, Purple White, Red, Green,Blue White, Red, Green Cable Diamter Dia:12 Dia:12 Dia:12 Lamp Holder E27 B15d B15d Protection Class IP56	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS ■ China Head Light: ■ Standards:	■ Product Advantage: ■ Main Specification:
---	---

China Head Light:



Used as lamp signal for navigation.

Product Advantage:

Screw-type connecting flange, convenient to install and replace the bulb, High quality pyres glass for lampshade.

Standards:

1. Confirm to the international regulation for preventing collision at sea, 1972 and grade entry norms for steel ships.
2. Confirm to the International Standard IEC60598-1-2008.
3. Confirm to the standard of marine electric signal light's technical condition GB/T 3028-2012.

Main Specification:

Type	CXH5-1	CXH5-1A	CXH5-1B	CXH5-2	CXH-2A	CXH-2B	CXH5-3
Visibility	3n.m	3n.m	3n.m	2n.m	2n.m	2n.m	2n.m
Level arc	360 ^o	360 ^o	360 ^o	360 ^o	360 ^o	360 ^o	360 ^o
Material	Aluminum	Plastic	Stainless Steel	Aluminum	Plastic	Stainless Steel	Plastic
Weight	0.9kgs	0.73kgs	1.73kgs	0.4kgs	0.5kgs	1.25kgs	0.3kgs
Voltage	24V,110V,220V			24V			24V,12V
Power	60W			30W			15W
Color	White, Red, Green, Yellow,Blue, Purple			Whire, Red, Green,Blue		White, Red, Green	
Cable Diamter	Dia:12			Dia:12			Dia:12
Lamp Holder	E27			B15d			B15d
Protection Class	IP56						