

MARINE WINCH

Heavy Duty Offshore Winch

Heavy Duty Offshore Winch complete, portable hydraulically controlled winch mounted on its foundation frame, ready for connection winch set of max. 8 identical winches (4 x left hand & 4 x right hand desi...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Winch
Standard	DIN
Material	Cast steel
Certificate	ABS,LR, BV, GL, CCS, RINA, IRS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Winch	Model / SKU	Heavy-Duty-Offshore-Winch
Standard	DIN	Material	Cast steel
Certificate	ABS,LR, BV, GL, CCS, RINA, IRS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- Heavy Duty Offshore Winch
 - winch set of max. 8 identical winches (4 x left hand & 4 x right hand design)
 - for local oil supply or on request also with own hydraulic power units
 - for the use of steel rope Ø 52mm, 1500m long
- complete, portable hydraulically controlled winch mounted on its foundation frame, ready for connection (on single foundations or also possible on a common foundation frame for more than one winch)
 - with spooling mechanism
 - static holding load (brake) 1500 kN in 1st layer

Heavy Duty Offshore Winch

- complete, portable hydraulically controlled winch mounted on its foundation frame, ready for connection**
- winch set of max. 8 identical winches (4 x left hand & 4 x right hand design)**
(on single foundations or also possible on a common foundation frame for more than one winch)
- for local oil supply or on request also with own hydraulic power units**
- with spooling mechanism**
- for the use of steel rope Ø 52mm, 1500m long**
- static holding load (brake) 1500 kN in 1st layer**
- stepless speed control**
- stalling pull 1000kN at 0 m/min**
- pull / speed 1st layer: 900 kN at 0-6 m/min, 160 kN at 0-30 m/min**
- 5th layer: 630 kN at 0-8.5 m/min, 110 kN at 0-42 m/min**
- 10th layer: 450 kN at 0-11 m/min, 80 kN at 0-55 m/min**
- dynamic braking for anchor rope paying out with water cooled brake**
- pull / speed 1st layer: 200 kN at 0-120 m/min**
- 5th layer: 140 kN at 0-170 m/min**
- 10th layer: 100 kN at 0-240 m/min**
- clutch, hydraulic remote control operation**
- disk brake, sea water cooled, adjustable, hydraulic, remote controlled**
- spindle band brake, hydraulic (remote control) as well as manual operation, spring loaded hydraulic cylinder**
- integrated transmitters for cable length, speed, working torque and brake torque**