

HAMMER UNION

HIGH, MEDIUM AND LOW PRESSURE UNIONS FIG100

ISO9001 Supplier

Class Certificate

Export Supply

HIGH, MEDIUM AND LOW PRESSURE UNIONS FIG100 The high pressure unions are made from high-strength alloy steel by forging by means of international advanced technologies. The strict heat treatment is adopted ...



Key Highlights

Category	Hammer Union
Standard	ASTM
Material	HIGH, MEDIUM AND LOW PRESSURE UNIONS FIG100 The high pressure unions are...
Weight / Size	They are recommended for occasions where the low pressure manifolds are ...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Hammer Union	Model / SKU	HIGH-MEDIUM-AND-LOW-PRESSURE-UNIONS-FIG100
Standard	ASTM	Material	HIGH, MEDIUM AND LOW PRESSURE UNIONS FIG100 The high pressure unions are made from high-strength alloy steel by forging by means of international advanced technologies.
Weight / Size	They are recommended for occasions where the low pressure manifolds are used and the working pressure is not more than 1000Psi SPECIFICATIONS AND REFERENCE SIZES OF UNION Type 100:1 OOOPSI NSCWP, test pressure:	Surface	Precision linear sealing surface guarantees reliable pressure seal.
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	■ HIGH, MEDIUM AND LOW PRESSURE UNIONS FIG100	■ SPECIFICATIONS AND REFERENCE SIZES OF UNION
----------	---	---

HIGH, MEDIUM AND LOW PRESSURE UNIONS FIG100

The high pressure unions are made from high-strength alloy steel by forging by means of international advanced technologies. The strict heat treatment is adopted to guarantee the joint to have the uniform metallographic structure and bearing capacity.Used materials completely conform to American ASTM and ASI standards, The technical indexes of the product completely conform to API Spec 16c standard. The product is characterized by reliable seal, rapid assembly and disassembly and good compatibility and interchangeability. In addition, the product joint can be connected by pipe line thread, oil tube thread, butt-welded or non-pressure sealed end.

Precision linear sealing surface guarantees reliable pressure seal. They are recommended for occasions where the low pressure manifolds are used and the working pressure is not more than 1000Psi

SPECIFICATIONS AND REFERENCE SIZES OF UNION

标称管道尺寸 Nominal pipe size		总长 Total length		螺母半径 Nut radius		材料 Material		重量 Weight	
						螺母 Nut	零件 Part		
in	mm	in	mm	in	mm			lb	kg
2	50.5	3 ⁵ / ₈	92.1	2 ¹⁵ / ₁₆	74.6	SF	SF	5.25	2.4
2 ¹ / ₂	63.8	4 ¹ / ₄	108.0	3 ³ / ₈	92.1	SF	SF	8.0	3.6
3	76.2	4 ¹⁵ / ₁₆	125.4	4 ¹ / ₁₆	103.2	SF	SF	14.0	6.4
4	101.6	5 ¹⁵ / ₁₆	150.8	4 ²⁵ / ₃₂	121.4	SF	SF	23.0	10.4
6	152.4	6 ⁵ / ₈	168.3	6 ⁷ / ₁₆	163.5	SF	SF	44.5	20.2
8	203.2	7 ¹ / ₄	184.2	7 ¹¹ / ₁₆	195.3	SF	SF	61.0	27.7

Type 100:1 OOOPSI NSCWP, test pressure: 1500PSI, black nut and yellow part.