

ANCHOR CHAIN

Hot Dip Galvanized Anchor Chain

Hot Dip Galvanized(HDG) Anchor Chain has the good feature of anti-corrosion, size range from 12.5mm to 76mm. HDG Finish is made according to client request, please inform when inquiry. We supply the HDG Anchor Chain to M...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Anchor Chain
Standard	DIN
Material	Steel Bars
Weight / Size	Hot Dip Galvanized(HDG) Anchor Chain has the good feature of anti-corros...
Certificate	LR, ABS, BV,DNVGL,NK,

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Anchor Chain	Model / SKU	Hot-Dip-Galvanized-Anchor-Chain
Standard	DIN	Material	Steel Bars
Weight / Size	Hot Dip Galvanized(HDG) Anchor Chain has the good feature of anti-corrosion, size range from 12.5mm to 76mm.	Surface	Hot Dip Galvanized
Certificate	LR, ABS, BV,DNVGL,NK,	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

■ China Hot Dip Galvanized Anchor Chain:

■ HDG Anchor Chain Size

China Hot Dip Galvanized Anchor Chain:

Hot Dip Galvanized(HDG) Anchor Chain has the good feature of anti-corrosion, size range from 12.5mm to 76mm. HDG Finish is made according to client request, please inform when inquiry. We supply the HDG Anchor Chain to Malaysia, Singapore, Indonesia, Thailand and other countries.

Delivery time usually is 15-25 days, packed by tonne bags and shipped by sea.



HDG Anchor Chain Size

Chain Diameter mm	Proof Load		Breaking Load		Chain Diameter mm	Minimum Weight Kg per lenght of 27,5 m
	Grade 2 kN	Grade 3 kN	Grade 2 Kn	Grade 3 kN		
12.5	66	-	92	-	12.5	98
14	82	-	116	-	14	119
16	107	150	150	216	16	160
17.5	127	179	179	256	17.5	190
19	150	211	211	301	19	225
20.5	175	244	244	349	20.5	265
22	200	280	280	401	22	300
24	237	332	332	476	24	360
26	278	389	389	556	26	420
28	321	449	449	642	28	490
30	368	514	514	735	30	565
32	417	583	583	833	32	635
34	468	655	655	937	34	720
36	523	732	732	1050	36	800
38	581	812	812	1160	38	895
40	640	896	896	1280	40	995

42	703	981	981	1400	42	1100
44	769	1080	1080	1540	44	1200
46	837	1170	1170	1680	46	1320
48	908	1280	1280	1810	48	1440
50	981	1370	1370	1960	50	1560
52	1060	1480	1480	2110	52	1675
54	1140	1590	1590	2270	54	1820
56	1220	1710	1710	2430	56	1935
58	1290	1810	1810	2600	58	2075
60	1380	1940	1940	2770	60	2220
62	1470	2060	2060	2940	62	2365
64	1560	2190	2190	3130	64	2550
66	1660	2310	2310	3300	66	2695
68	1750	2450	2450	3500	68	2890
70	1840	2580	2580	3690	70	3030
73	1990	2790	2790	3990	73	3290
76	2150	3010	3010	4300	76	3555

