

HIGH PRESSURE PUMP

HPU-225 Pneumatic Hydraulic High Pressure Pump

ISO9001 Supplier

Class Certificate

Export Supply

HPU-225 Pneumatic Hydraulic High Pressure Pump HPU-225 pneumatic hydraulic high pressure pump is a new type of hydraulic stretching and pressing process equipment. It converts the lower air pressure into pressure o...



Key Highlights

Category	High Pressure Pump
Standard	DIN
Weight / Size	It can be widely used for fastening large and medium-sized mechanical sc...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	High Pressure Pump	Model / SKU	HPU-225-Pneumatic-Hydraulic-High-Pressure-Pump
Standard	DIN	Weight / Size	It can be widely used for fastening large and medium-sized mechanical screws and keyless matching of large transmission parts and structural parts in manufacturing industries such as metallurgy, mining, petrochemical industry, shipbuilding industry, locomotive and rolling stock.
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	■ HPU-225 Pneumatic Hydraulic High Pressure Pump	■ Specification:
-----------------	--	------------------

HPU-225 Pneumatic Hydraulic High Pressure Pump

HPU-225 pneumatic hydraulic high pressure pump is a new type of hydraulic stretching and pressing process equipment. It converts the lower air pressure into pressure oil and becomes an ideal power source.

HPU-225 pneumatic hydraulic high pressure pump has the advantages of high output pressure, simple operation, safety and reliability, convenient carrying and so on. It can be widely used for fastening large and medium-sized mechanical screws and keyless matching of large transmission parts and structural parts in manufacturing industries such as metallurgy, mining, petrochemical industry, shipbuilding industry, locomotive and rolling stock. It is time-saving, labor-saving, uniform force distribution and reliable sealing. It is an ideal tool for the assembly and matching of various large and medium-sized machinery

Specification:

Model	HPU-225 pneumatic hydraulic high pressure pump
Output pressure	Maximum 225 MPa (input air pressure 0.9MPa)
Pump operating speed	About 450 cycles / min (input air pressure 0.8MPa)
Oil supply per cycle	0.8ml
Air consumption	1.05x L / min (input air pressure 0.8MPa)
Tank capacity	Approx. 4.5 litres
Maximum flow (air pressure)	About 0.35 L / min (input air pressure 0.8MPa)
Weightt	28KG (net weight)
Size	430×370×415mm