

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

ELECTRIC HEATER

HS30 Marine Dough Mixer

HS30 Marine Dough Mixer Product introduction: 1. The shell is made of aluminum alloy die-casting, fast heat dissipation, quiet operation and smooth, good stability, double shell paint; 2....

- ISO9001 Supplier
- Class Certificate
- Export Supply

	<h3 style="margin: 0;">Key Highlights</h3> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="background-color: #1a3d4d; color: white; padding: 5px;">Category</td> <td style="padding: 5px;">Electric Heater</td> </tr> <tr> <td style="background-color: #1a3d4d; color: white; padding: 5px;">Standard</td> <td style="padding: 5px;">DIN</td> </tr> <tr> <td style="background-color: #1a3d4d; color: white; padding: 5px;">Material</td> <td style="padding: 5px;">SS304</td> </tr> <tr> <td style="background-color: #1a3d4d; color: white; padding: 5px;">Weight / Size</td> <td style="padding: 5px;">Model Dimension(mm) Capacity (L) Power (kw) Volts(v) HZ N/W(kg) HS20 69...</td> </tr> <tr> <td style="background-color: #1a3d4d; color: white; padding: 5px;">Certificate</td> <td style="padding: 5px;">ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS</td> </tr> </table> <p style="font-size: small; margin-top: 10px;">We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.</p>	Category	Electric Heater	Standard	DIN	Material	SS304	Weight / Size	Model Dimension(mm) Capacity (L) Power (kw) Volts(v) HZ N/W(kg) HS20 69...	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Category	Electric Heater										
Standard	DIN										
Material	SS304										
Weight / Size	Model Dimension(mm) Capacity (L) Power (kw) Volts(v) HZ N/W(kg) HS20 69...										
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS										

Technical Specifications			
Category	Electric Heater	Model / SKU	HS30-Marine-Dough-Mixer
Standard	DIN	Material	SS304
Weight / Size	Model Dimension(mm) Capacity (L) Power (kw) Volts(v) HZ N/W(kg) HS20 690X380X730 20 0.75 220V-1P 50/60Hz 70 HS30 730X430X770 30 1.1 220V/380V/415V/440V-1P/3P 50/60Hz 90 HS40 870X480X935 40 2.2 380V/415V/440V-3P 50/60Hz 127 HS50 920X530X935 50 2.2 380V/415V/440V-3P 50/60Hz 130	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

■ Product introduction:

■ Technical data:

Product introduction:

1. The shell is made of aluminum alloy die-casting, fast heat dissipation, quiet operation and smooth, good stability, double shell paint;
2. The original Japanese timer, France TE control switch products and accessories quality certification, beautiful and durable;
3. The strong double motor design, two phase transmission system with high efficiency, low noise, strong horse;
4. The automatic power-off, especially safety protection net;
5. The spiral hook adopts precision casting, molding, sturdy and durable;
6. The casing using bending welding molding plate, the fuselage through special anti rust treatment;
7. It can remove the installation foot.

Technical data:

Model	Dimension(mm)	Capacity (L)	Power (kw)	Volts(v)	HZ	N/W(kg)
HS20	690X380X730	20	0.75	220V-1P	50/60Hz	70
HS30	730X430X770	30	1.1	220V/380V/415V/440V-1P/3P	50/60Hz	90
HS40	870X480X935	40	2.2	380V/415V/440V-3P	50/60Hz	127
HS50	920X530X935	50	2.2	380V/415V/440V-3P	50/60Hz	130