

MARINE HOIST

HSH-A820 Serie Level Hoist

Standard Features:The design is in accordance with EN13157 standard,it meets all pertinent world standards. High strength steel frame and gear case build to be durable for rugged needs of construction and maintenance ri...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Hoist
Standard	ISO
Material	G80 Chain
Weight / Size	Model H005-A820 H0075-A820 H010-A820 H015-A820 H020-A820 H030-A820 H060-...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Marine Hoist	Model / SKU	HSH-A820-Serie-Level-Hoist
Standard	ISO	Material	G80 Chain
Weight / Size	Model H005-A820 H0075-A820 H010-A820 H015-A820 H020-A820 H030-A820 H060-A820 H090-A820 Capacity Tons 0.5 0.75 1 1.5 2 3 6 9 Load Chain mm 6x18 6x18 6x18 8x24 8x24 10x30 10x30 10x30 Strands of load chain 1 1 1 1 1 1 2 3 Strands of lift mm 1.5 1.5 1.5 1.5 1.5 1.5 1.5 1.5 Load chain distance by rotating the hand wheel one circle mm 19.8 19.8 19.8 21.3 21.3 16.8 8.4 5.6 Effort required to lift rated load N 180 270 360 295 393 335 370 420 Running test load KN 6.13 9.2 12.3 18.4 24.5 36.8 73.5 110.3 Dimensions(mm) A 158 158 158 176 176 198 198 198 B 97.5 97.5 97.5 102 102 112 112 112 C 135 135 162 162 211 254 319 D 34 40 40 45 50 55 65 85 Hmin 300 320 320 380 380 480 620 700 L 250 250 250 270 270 430 430 430 K 21 26 26 30 30 38 44 50 Extra weight per meters of extra lift 0.8 0.8 0.8 1.4 1.4 2.2 4.3 6.5 Net weight 6.8 7.3 7.3 10.6 10.9 20 29 42.4	Surface	Special surface treatment of spare parts.
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

China HSH-A820 Serie Level Hoist:

Standard Features:The design is in accordance with EN13157 standard,it meets all pertinent world standards. High strength steel frame and gear case build to be durable for rugged needs of construction and maintenance rigging. 360 degree handle rotation with short stroke to ratchet loads. Equipped with wide throat top and bottom drop forged hooks that are designed to bend slowly to warn of overloads.Load chain is alloy steel grade 80 accord with ISO16877 standard. Optional features:.Caged ball bearing on load sheaves. Cast safety latches. Thrust bearing in bottom hook assembly. Load chain is alloy steel grade 80 accord with EN818-7 standard. Special surface treatment of spare parts.

Model	H005-A820	H0075-A820	H010-A820	H015-A820	H020-A820	H030-A820	H060-A820	H090-A820	
Capacity	Tons	0.5	0.75	1	1.5	2	3	6	9
Load Chain	mm	6x18	6x18	6x18	8x24	8x24	10x30	10x30	10x30
Strands of load chain		1	1	1	1	1	1	2	3
Strands of lift	mm	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5
Load chain distance by rotating the hand wheel one circle	mm	19.8	19.8	19.8	21.3	21.3	16.8	8.4	5.6
Effort required to lift rated load	N	180	270	360	295	393	335	370	420
Running test load	KN	6.13	9.2	12.3	18.4	24.5	36.8	73.5	110.3
Dimensions(mm)	A	158	158	158	176	176	198	198	198
	B	97.5	97.5	97.5	102	102	112	112	112
	C	135	135	135	162	162	211	254	319
	D	34	40	40	45	50	55	65	85
	Hmin	300	320	320	380	380	480	620	700
	L	250	250	250	270	270	430	430	430
	K	21	26	26	30	30	38	44	50
Extra weight per meters of extra lift		0.8	0.8	0.8	1.4	1.4	2.2	4.3	6.5
Net weight		6.8	7.3	7.3	10.6	10.9	20	29	42.4

