

FIRE DETECTION AND ALARM SYSTEM

HY-M900K Flush Type Manual Fire Alarm Button

ISO9001 Supplier

Class Certificate

Export Supply

Color: Red Shell Material: ABS Fire Retardant Cable Gland: 2-PG16 Voltage: DC15V-33V  
Current: <=5uA Alarm Current: <=30mA



Key Highlights

|             |                                            |
|-------------|--------------------------------------------|
| Category    | Fire Detection and Alarm System            |
| Standard    | EN                                         |
| Material    | Red Shell Material:                        |
| Certificate | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

|             |                                            |             |                                              |
|-------------|--------------------------------------------|-------------|----------------------------------------------|
| Category    | Fire Detection and Alarm System            | Model / SKU | HY-M900K-Flush-Type-Manual-Fire-Alarm-Button |
| Standard    | EN                                         | Material    | Red Shell Material:                          |
| Certificate | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS | Warranty    | 12 Months unless specified otherwise         |
| Origin      | China                                      |             |                                              |

China HY-M900K Flush Type Manual Fire Alarm Button:

Color: Red  
Shell Material: ABS Fire Retardant  
Cable Gland: 2-PG16  
Voltage: DC15V-33V  
Current: <=5uA  
Alarm Current: <=30mA

