

LIFEBOAT DAVIT

Hydraulic Telescopic Folding Arm Crane And Rescue Boat Winch

ISO9001 Supplier

Class Certificate

Export Supply

Product description: 1.crane technical data Max hoisting load:2.5 ton. Slewing radius: 2~10meter Max slewing angle: <360 degree(with limit switch) Hoisting speed:≥20 meter / minute ...



Key Highlights

Category	Lifeboat Davit
Standard	DIN
Material	50 meter Steel wire rope size:18x19-16-1770 Slewing speed:0~1 r/minute L...
Weight / Size	50 meter Steel wire rope size:18x19-16-1770 Slewing speed:0~1 r/minute L...
Certificate	CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Lifeboat Davit	Model / SKU	Hydraulic-Telescopic-Folding-Arm-Crane-And-Rescue-Boat-Winch
Standard	DIN	Material	50 meter Steel wire rope size:18x19-16-1770 Slewing speed:0~1 r/minute Luffi ng time:
Weight / Size	50 meter Steel wire rope size:18x19-16-1770 Slewing speed:0~1 r/minute Luffi ng time:	Certificate	CCS
Warranty	12 Months unless specified otherwise	Origin	China

Product description:

1.crane technical data

Max hoisting load:2.5 ton.

Slewing radius: 2~10meter

Max slewing angle: <360 degree(with limit switch)

Hoisting speed:≥20 meter / minute

Hoisting height: 50 meter

Steel wire rope size:18x19-16-1770

Slewing speed:0~1 r/minute

Luffing time: about 45s

Folding time: about 45s

Design angle: heel 5 degree, trim 2 degree

Motor model of oil pump:y180l-4-h

2.rescue boat davit technical data

Max working load: 27.5kn

Slewing radius: 8m

Hoisting load: 27.5kn

Slewing load: 27.5kn

Hoisting speed:≥18m/min

Lowering speed:40~60m/min

Size of wire-rope:16- 19 18- 1570

Hoisting height: 30 m

Slewing angle from accumulator :≤18 00

Slewing speed by accumulator driven:≥0.5r/min

Slewing speed by motor driven:0-1r/min

Design angle: heel 20 degree, trim 10 degree