

ELECTRIC HEATER

HZ Type Flat Heater

HZ Type Flat Heater HZ type flat-plate heater is a new multi-function heater used for heating bearings. Mainly used for heating of small bearings and other small parts. Its appearance is like a suitcase,...

ISO9001 Supplier

Class Certificate

Export Supply



jinbomarine.com

Key Highlights

Category	Electric Heater
Standard	EN
Weight / Size	This heating device is compact, safe to use, and will not overheat even ...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Electric Heater	Model / SKU	HZ-Type-Flat-Heater
Standard	EN	Weight / Size	This heating device is compact, safe to use, and will not overheat even if left unattended. Voltage Current Power Temperature range Precision Heating plate size Weight Dimensions 220V 10A 2.2kW 0-200°C ±5°C 350x300mm 18kg 510x300×160mm
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

China HZ Type Flat Heater:

HZ Type Flat Heater

HZ type flat-plate heater is a new multi-function heater used for heating bearings. Mainly used for heating of small bearings and other small parts. Its appearance is like a suitcase, and there is a shelf inside,which is a heating plate, which is heated by an electric heating tube. Its temperature is adjustable and can be precisely controlled to ensure that the bearing temperature does not exceed 120. The bearings are heated on a heating plate. In order to make the temperature uniform, it is best to turn the bearing several times during the heating process. There is a cover on the plate, which plays the role of heat preservation and preventing the bearing from being polluted. This heating device is compact, safe to use, and will not overheat even if left unattended.

Voltage	Current	Power	Temperature range	Precision	Heating plate size	Weight	Dimensions
220V	10A	2.2kW	0-200℃	±5℃	350x300mm	18kg	510x300×160 mm