TURNBUCKLE

JIS F 3403 Rigging Screws

Drop forged frame with a solid thimnle and bolt ends, Rigging Scews used for standing rigging of ships' mast and post. Please specify the diameter of wirel rope to be used when ording, also please specify galvanize...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Turnbuckle
Standard	JIS
Material	Rigging Screws Construction and Material Specification Nominal Size Dia.
Weight / Size	Rigging Screws Construction and Material Specification Nominal Size Dia.
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Turnbuckle	**Model / SKU**	JIS-F-3403-Rigging-Screws
Standard	JIS	**Material**	Rigging Screws Construction and Material Specification Nominal Size Dia.
Weight / Size	Rigging Screws Construction and Material Specification Nominal Size Dia.	**Surface**	galvanized
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	**Warranty**	12 Months unless specified otherwise
Origin	China		

CONTENTS

- China JIS F 3403 Rigging Screws:
- Specification
- Rigging Screws Construction and Material

China JIS F 3403 Rigging Screws:

Drop forged frame with a solid thimnle and bolt ends, Rigging Scews used for standing rigging of ships' mast and post.

Please specify the diameter of wirel rope to be used when ording, also please specify galvanized or ungalvanized.

Rigging Screws Construction and Material

Specification

Nominal Size	Dia. Of Wire Rope	Nomial Size of Wire Socket	SWL(Ton)	Weight(Kg)
14	14	2.1	5.97	
16	16	16	2.6	8.58
18	18	18	3.3	11.6
22	20-22.4	20-22	5.5	14.8
24	24	24	5.9	19.4
26	25	26	6.9	23.9
30	28-30	28-30	9.2	30.2
32	32	32	10.5	43.2
36	36	36	13	51.1
38	38	38	14.5	59.9
40	40	40	16.5	70.7
42	42.5	42	18.5	93.5
45	45	45	21	105
48	47.5	48	23	117
50	50	50	25.5	124

