

STERN TUBE SEAL

JQ/CS 49 Type Stern Tube seal

Product Application When inland water vessels have oil as their lubricating working medium and do not have a large stern shatf,this type of apparatuses is suggested to be chosen.

Product Specification ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Stern Tube Seal
Standard	EN
Weight / Size	Product Specification Model D A B C F H K N P S T n d n1 Weight (kg) Fro...
Certificate	BV, ABS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Stern Tube Seal	Model / SKU	JQ-CS-49-Type-Stern-Tube-seal
Standard	EN	Weight / Size	Product Specification Model D A B C F H K N P S T n d n1 Weight (kg) Front Back 130JQ/CS49 130 320 290 250 145 28 140 160 215 230 200 8 11 8 26 38 150JQ/CS49 150 345 310 270 165 28 145 180 235 250 220 8 11 8 29 42 170JQ/CS49 170 366 336 292 185 28 150 200 260 270 240 12 13 8 34 46 190JQ/CS49 190 390 360 320 205 28 160 220 290 295 260 12 13 8 40 53 210JQ/CS49 210 410 380 335 225 32 160 246 310 320 280 16 13 12 45 59 230JQ/CS49 230 445 410 370 245 32 170 266 350 340 300 16 15 12 53 66 250JQ/CS49 250 475 440 390 270 34 175 290 370 360 326 16 17 12 60 73 280JQ/CS49 280 505 470 420 300 34 180 320 400 390 356 16 17 12 68 82 320JQ/CS49 320 550 510 460 340 34 180 360 440 430 390 16 22 12 76 90 360JQ/CS49 360 590 550 500 380 36 180 405 480 470 430 16 22 12 84 98 For more details, please contact us.
Certificate	BV, ABS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		


CONTENTS	Product Application	Product Specification
----------	---	---

Product Application

When inland water vessels have oil as their lubricating working medium and do not have a large stern shaft,this type of apparatuses is suggested to be chosen.


Product Specification





说明：
长江及内河航行的船舶，且润滑工作介质为油类，建议选用该类型装置。
Remarks:
This type of apparatuses is suitable for vessels in inland water whose lubricating working medium is oil.

JQ/CS 49后密封装置
JQ/CS 49 aft sealing apparatus



JQ/CS 49前密封装置
JQ/CS 49 forward sealing apparatus

Model	D	A	B	C	F	H	K	N	P	S	T	n	d	n1	Weight (kg)	
															Front	Back
130JQ/CS49	130	320	290	250	145	28	140	160	215	230	200	8	11	8	26	38
150JQ/CS49	150	345	310	270	165	28	145	180	235	250	220	8	11	8	29	42
170JQ/CS49	170	366	336	292	185	28	150	200	260	270	240	12	13	8	34	46
190JQ/CS49	190	390	360	320	205	28	160	220	290	295	260	12	13	8	40	53
210JQ/CS49	210	410	380	335	225	32	160	246	310	320	280	16	13	12	45	59
230JQ/CS49	230	445	410	370	245	32	170	266	350	340	300	16	15	12	53	66
250JQ/CS49	250	475	440	390	270	34	175	290	370	360	326	16	17	12	60	73
280JQ/CS49	280	505	470	420	300	34	180	320	400	390	356	16	17	12	68	82
320JQ/CS49	320	550	510	460	340	34	180	360	440	430	390	16	22	12	76	90
360JQ/CS49	360	590	550	500	380	36	180	405	480	470	430	16	22	12	84	98

For more details, please contact us.