

FIRE DETECTION AND ALARM SYSTEM

JTW-ZD-1330 Point Heat Fire Detector

JTW-ZD-1330 Point Heat Fire Detector Model : JTW-ZD-1330 Static current : ≤350μA Alarm current : ≤3.5mA Working voltage : DC15 - 32V Hull material : ABS fire resistance Colour : cream...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Fire Detection and Alarm System
Standard	EN
Material	JTW-ZD-1330 Point Heat Fire Detector Model : JTW-ZD-1330 Static current : ≤...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Fire Detection and Alarm System	Model / SKU	JTW-ZD-1330-Point-Heat-Fire-Detector
Standard	EN	Material	JTW-ZD-1330 Point Heat Fire Detector Model : JTW-ZD-1330 Static current : ≤350μA Alarm current : ≤3.5mA Working voltage : DC15 - 32V Hull material : ABS fire resistance Colour : cream-colored
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

China JTW-ZD-1330 Point Heat Fire Detector:

JTW-ZD-1330 Point Heat Fire Detector

Model : JTW-ZD-1330

Static current : $\leq 350\mu\text{A}$

Alarm current : $\leq 3.5\text{mA}$

Working voltage : DC15 - 32V

Hull material : ABS fire resistance

Colour : cream-colored