

FIRE DETECTION AND ALARM SYSTEM

JTW-ZD-1332 JTW-ZD-1333 Point Heat Fire Detector

ISO9001 Supplier

Class Certificate

Export Supply

JTW-ZD-1332 JTW-ZD-1333 Point Heat Fire Detector Model: JTW-ZD-1332,JTW-ZD-1333  
Sensitivity: 60°C,90°C Static current: ≤120μA Alarm current: ≤18.5mA Working voltage:  
DC8.5~28V Hul...



Key Highlights

|             |                                                      |
|-------------|------------------------------------------------------|
| Category    | Fire Detection and Alarm System                      |
| Standard    | EN                                                   |
| Material    | DC8.5~28V Hull material: ABS fire resistance Colour: |
| Certificate | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS           |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

|             |                                            |             |                                                      |
|-------------|--------------------------------------------|-------------|------------------------------------------------------|
| Category    | Fire Detection and Alarm System            | Model / SKU | JTW-ZD-1332-JTW-ZD-1333-Point-Heat-Fire-Detector     |
| Standard    | EN                                         | Material    | DC8.5~28V Hull material: ABS fire resistance Colour: |
| Certificate | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS | Warranty    | 12 Months unless specified otherwise                 |
| Origin      | China                                      |             |                                                      |

China JTW-ZD-1332 JTW-ZD-1333 Point Heat Fire Detector:

JTW-ZD-1332 JTW-ZD-1333 Point Heat Fire Detector

Model: JTW-ZD-1332,JTW-ZD-1333

Sensitivity: 60°C,90°C

Static current: ≤120μA

Alarm current:  $\leq 18.5\text{mA}$

Working voltage: DC8.5~28V

Hull material: ABS fire resistance

Colour: cream-colored