

FIRE DETECTION AND ALARM SYSTEM

JTY-GDF1322Ex Point Smoke detector

JTY-GDF1322Ex Point Smoke detector Model: JTY-GDF1322Ex Static current: ≤120μA Alarm current: ≤93mA Ex rating: Ex ib II C T5/T6 Gb Working voltage: DC8.5~28V Hull material: ABS ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Fire Detection and Alarm System
Standard	GB
Material	DC8.5~28V Hull material:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Fire Detection and Alarm System	Model / SKU	JTY-GDF1322Ex-Point-Smoke-detector
Standard	GB	Material	DC8.5~28V Hull material:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

China JTY-GDF1322Ex Point Smoke detector:

JTY-GDF1322Ex Point Smoke detector

Model: JTY-GDF1322Ex

Static current: ≤120μA

Alarm current: ≤93mA

Ex rating: Ex ib II C T5/T6 Gb

Working voltage: DC8.5~28V

Hull material: ABS fire resistance

Colour: cream-colored