

HAND PUMP

KCB-200 Marine Gear Pump

 KCB series of gear pumps is used to deliver non-corrosive lubricating oil at temperature below 80°C or equivalent liquid without solid particles and fibres and with the viscosity of 5-1500CST. ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Hand Pump
Standard	CB
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Hand Pump	Model / SKU	KCB-200-Marine-Gear-Pump
Standard	CB	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

China KCB-200 Marine Gear Pump:

KCB series of gear pumps is used to deliver non-corrosive lubricating oil at temperature below 80°C or equivalent liquid without solid particles and fibres and with the viscosity of 5-1500CST.

Main Technical Data				
Model	Pump flow rate (L/min)	Rev speed (r/min)	Discharge pressuer (Mpa)	Motor power (KW)
KCB-18.3	18.3	1400	1.45	1.5
2CY-1.1/1.45	18.3	1400	1.45	1.5
KCB-33.3	33.3	1420	1.45	2.2

2CY-2/1.45	33.3	1420	1.45	2.2
KCB-55	55	1400	0.33	1.5
2CY-3.3/0.33	55	1400	0.33	1.5
2CY-3.3/0.8	55	1420	0.8	3
KCB-83.3	83.3	1400	0.33	2.2
2CY-5/0.33	83.3	1400	0.33	2.2
2CY-5/0.8	83.3	1420	0.8	4
KCB-200	200	1420	0.33	4
2CY-12/0.33	200	1440	0.33	4

