

GEAR PUMP

LB Series Gear Pump for Refrigerator

LR Series Gear Pump is used for transferring N32 or N46 refrigerated lubricating and lubricant oil, temperature range from 10°C to 80 °C Main Specification Type ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Gear Pump
Standard	EN
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Gear Pump	Model / SKU	LB-Series-Gear-Pump-for-Refrigerator
Standard	EN	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

- China LB Series Gear Pump for Refrigerator:
- Main Specification

China LB Series Gear Pump for Refrigerator:



LR Series Gear Pump is used for transferring N32 or N46 refrigerated lubricating and lubricant oil, temperature range from 10°C to 80 °C

Main Specification

Type	Suction/Extrude Port Diameter	Capacity		Differential Pressure	Max. Discharge Pressure	Motor Power	Motor Speed	Motor Model
	mm	m3/h	L/min	Mpa	Mpa	kw	r/min	
LB1.8	20	1.8	30	0.5	2.5	0.55	1390	Y801-4
LB3.6	25	3.6	60	0.5	2.5	1.1	910	Y90L-6
LB10	40	10	166.7	0.5	2.5	3	1420	Y100L2-4
LB12	40	12	200	0.5	2.5	3	1420	Y100L2-4
LB20	80	20	333.3	0.5	2.5	5.5	960	Y132M2-6
LB25	80	25	416.7	0.5	2.5	7.5	970	Y160M-6
LB40	100	40	666.7	0.5	2.5	11	970	Y160L-6