

MARINE DECK COVERING

Lightweight Primary Deck Covering

Main Specification No. Item name Index Standard 1 Initial setting time ≥1h...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Deck Covering
Standard	EN
Material	Dry material (A component):
Weight / Size	Item name Index Standard 1 Initial setting time ≥1h Q/HCF1-2004 2 Final ...
Certificate	ABS,LR, BV, GL CCS
We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.	

Technical Specifications

Category	Marine Deck Covering	Model / SKU	Lightweight-Primary-Deck-Covering
Standard	EN	Material	Dry material (A component):
Weight / Size	Item name Index Standard 1 Initial setting time ≥1h Q/HCF1-2004 2 Final setting time ≤12h 3 Modulus of rapture ≥3MPa 4 Compressive strength ≥10MPa 5 Density ≤1300kg/m3 6 Water absorption ≤10% 7 Oil absorption ≤5% 8 Heat conductivity ≤1.2W/m.k 9 Not readily ignitability, smoke & toxicity In accordance with IMO.FTPC Parts 2,6/IMO.A 687(17) 10 Weight per square meter ≤16kg/10mm/m2 Features Characteristic:	Certificate	ABS,LR, BV, GL CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

■ China Lightweight Primary Deck Covering:

■ Features

■ Consume amount:

China Lightweight Primary Deck Covering:



Main Specification

No.	Item name	Index	Standard
1	Initial setting time	$\geq 1\text{h}$	Q/HCF1-2004
2	Final setting time	$\leq 12\text{h}$	
3	Modulus of rupture	$\geq 3\text{MPa}$	
4	Compressive strength	$\geq 10\text{MPa}$	
5	Density	$\leq 1300\text{kg/m}^3$	
6	Water absorption	$\leq 10\%$	
7	Oil absorption	$\leq 5\%$	
8	Heat conductivity	$\leq 1.2\text{W/m.k}$	
9	Not readily ignitability, smoke & toxicity	In accordance with IMO.FTPC Parts 2,6/IMO.A 687(17)	
10	Weight per square meter	$\leq 16\text{kg/10mm/m}^2$	

Features

Characteristic: Low density, strong adhesion, elastic, not water penetration, abrasion resistance.

Applied: Covering for not readily ignitable deck of cabins

Consume amount:

16 kg/m²

Packing: Dry material (A component): 20kg/pack; Liquid(B component): 8.5kg/barrel

Storage: Cool and dry place, moisture-proof, the quality guarantee period is 6 months

Certificate: ABS、BV、CCS、DNV、EC、GL、KR、LR、NK.

For more details, please feel free to contact us.

