

PRESSURE WATER TANK

LR Approved SS304 Hydrophore

Product Description: This hydrophore can be used as marine fresh water tank or washing water tank, it can be used for suppling fresh warter or washing water for all presons of the ship. It is also can be formed a c...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Pressure Water Tank
Standard	DIN
Material	95°C Main Material SS304 Working Pressure 0.4 Mpa Surface Treatment Sandb...
Certificate	CCS,GL,BV etc.
We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.	

Technical Specifications

Category	Pressure Water Tank	Model / SKU	LR-Approved-SS304-Hydrophore
Standard	DIN	Material	95°C Main Material SS304 Working Pressure 0.4 Mpa Surface Treatment Sandblast Sa2.5 Working Temp.
Surface	95°C Main Material SS304 Working Pressure 0.4 Mpa Surface Treatment Sandblast Sa2.5 Working Temp.	Certificate	CCS,GL,BV etc.
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

- Product Description:
- Technical Parameters:

Product Description:

This hydrophore can be used as marine fresh water tank or washing water tank, it can be used for supplying fresh warter or washing water for all presons of the ship. It is also can be formed a complete set with air compressor and used for supplying fresh water for tall building.

Technical Parameters:

Classficion	LR Class	Hydraulic Test	0.6Mpa
Standard	CB455-91	Air Tightness Test	0.4Mpa
Volume	1.0 M³	Response Pressure of the Safety Valve	0.42Mpa
Design Temp.	95°C	Main Material	SS304
Working Pressure	0.4 Mpa	Surface Treatment	Sandblast Sa2.5
Working Temp.	50°C	Pump Model	1.5CWX-2
Working Medium	Water	Delivery Time	60 days