

CHAIN SLING

LS intense sling

Description Rope sling is small and flexible. It can be used for binding and lowering goods. It is applicable for operations in various environments. Technical Data &...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Chain Sling
Standard	DIN
Weight / Size	Technical Data Single-limb Sling Products code Diameter A (PA) B (PES) Ma...
Certificate	CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Chain Sling	Model / SKU	LS-intense-sling
Standard	DIN	Weight / Size	Technical Data Single-limb Sling Products code Diameter A (PA) B (PES) Max length(m) X=A/B (mm) Working load limit (kg) Working load limit (kg) LS010X 10 200 120 LS012X 12 250 160 LS014X 14 300 250 LS016X 16 450 400 LS018X 18 680 560 LS020X 20 900 800 LS022X 22 1200 1100 LS024X 24 1400 1280 LS026X 26 1600 1500 LS028X 28 1800 1600 LS030X 30 2000 1800 To be customized LS032X 32 2400 2000 LS034X 34 2600 2400 LS036X 36 3000 2600 LS038X 38 3300 3000 LS040X 40 3800 3600 LS042X 42 4200 3900 LS044X 44 4600 4300 LS046X 46 5000 4500 LS048X 48 5300 4800 LS050X 50 5800 5400 LS052X 52 6000 5600 LS054X 54 6300 6000 LS056X 56 6800 6300 LS058X 58 7000 6600 LS060X 60 7300 6800
Certificate	CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	■ Description	■ Technical Data
----------	---------------	------------------

Description

Rope sling is small and flexible. It can be used for binding and lowing goods.

It is applicable for operations in various in environments.

Technical Data

Single-limb Sling				
Products code	Diameter	A (PA)	B (PES)	Max length(m)
X=A/B	(mm)	Working load limit (kg)	Working load limit (kg)	
LS010X	10	200	120	

LS012X	12	250	160	
LS014X	14	300	250	
LS016X	16	450	400	
LS018X	18	680	560	
LS020X	20	900	800	
LS022X	22	1200	1100	
LS024X	24	1400	1280	
LS026X	26	1600	1500	
LS028X	28	1800	1600	
LS030X	30	2000	1800	To be customized
LS032X	32	2400	2000	
LS034X	34	2600	2400	
LS036X	36	3000	2600	
LS038X	38	3300	3000	
LS040X	40	3800	3600	
LS042X	42	4200	3900	
LS044X	44	4600	4300	
LS046X	46	5000	4500	
LS048X	48	5300	4800	
LS050X	50	5800	5400	
LS052X	52	6000	5600	
LS054X	54	6300	6000	
LS056X	56	6800	6300	
LS058X	58	7000	6600	
LS060X	60	7300	6800	