

MEASUREMENT AND CONTROL DEVICE

LXZ Type Spiral Rotor Flowmeter

Product Description: It is a latest volume type flow meter, it adopt one pair special dentiform spiral rotor. It features pulseless, low voice,high accuracy, high reliability,large flow,high environmental suitabilit...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Measurement And Control Device
Standard	GB
Material	Nominal diameter" DN25 to 300mm Body material:
Certificate	CCS,GL,LR,BV,ABS,DNV GL,RINA,NK,KR ETC.

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Measurement And Control Device	Model / SKU	LXZ-Type-Spiral-Rotor-Flowmeter
Standard	GB	Material	Nominal diameter" DN25 to 300mm Body material:
Certificate	CCS,GL,LR,BV,ABS,DNV GL,RINA,NK,KR ETC.	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

■ Product Description:

■ Main Technical Specification:

Product Description:

It is a latest volume type flow meter, it adopt one pair special dentiform spiral rotor. It features pulseless, low voice,high accuracy, high reliability,large flow,high environmental suitability etc. It is mainly used for the commercial trade measurment and project management control of ship, petroleam,electric,dock etc.

Main Technical Specification:

Accuracy : 0.5 (0.2)

PN: 1.6 , 2.5 , 4.0Mpa

Working temperature: -20 to 60, 60 to 100, 100 to 200 centigrade.

Nominal diameter" DN25 to 300mm

Body material: ZG25

Rotor material: HT250

Bearing: graphite.

Local explosion proof class for remote indication: EXIA IICT5

Flange standard: GB2506-89