

MANUAL OPERATED FIRE MONITOR

Manual Fire Monitor PS80-HM

Type:PS80-HM-AN Flow Range :0-80L/S Automatic Nozzle (0-1250GPM) Working Pressure : 10 bar Max Reach @ Max Flow : 80m Range Of Motion : -90°~+90°Vert , 360°Rot Max Fog Angle : 120° Horizontal Control : Lever Action...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Manual Operated Fire Monitor
Standard	EN
Material	-90°~+90°Vert , 360°Rot Max Fog Angle : 120° Horizontal Control : Lever ...
Weight / Size	-90°~+90°Vert , 360°Rot Max Fog Angle : 120° Horizontal Control : Lever ...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Manual Operated Fire Monitor	Model / SKU	Manual-Fire-Monitor-PS80-HM
Standard	EN	Material	-90°~+90°Vert , 360°Rot Max Fog Angle : 120° Horizontal Control : Lever Action Rotational Lock Material (body) : Aluminum Material (Gear) : Aluminum Material (nozzle) : Aluminum, Adjustable Material (handwheel) : plastic Pump Requirement For Minimum Performance : 80L/S@ 8 bar Pipe dimensions for installation :
Weight / Size	-90°~+90°Vert , 360°Rot Max Fog Angle : 120° Horizontal Control : Lever Action Rotational Lock Material (body) : Aluminum Material (Gear) : Aluminum Material (nozzle) : Aluminum, Adjustable Material (handwheel) : plastic Pump Requirement For Minimum Performance : 80L/S@ 8 bar Pipe dimensions for installation :	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

China Manual Fire Monitor PS80-HM:

Type:PS80-HM-AN
Flow Range :0-80L/S Automatic Nozzle (0-1250GPM)
Working Pressure : 10 bar
Max Reach @ Max Flow : 80m
Range Of Motion : -90°~+90°Vert , 360°Rot
Max Fog Angle : 120°
Horizontal Control : Lever Action Rotational Lock
Material (body) : Aluminum
Material (Gear) : Aluminum
Material (nozzle) : Aluminum, Adjustable
Material (handwheel) : plastic
Pump Requirement For Minimum Performance : 80L/S@ 8 bar
Pipe dimensions for installation : 4 Inch
Monitor Inlet : DN100 flange
Monitor Outlet : 2.5 inch (65mm)
Paint : Fire Red

