

MANUAL OPERATED FIRE MONITOR

Manual Monitor PS30-50A

Type: PS30-50A Flow Range: 30-40-50 L/S Adjustable Working Pressure: 10 bar Max Reach @ Max Flow: 65m Range of motion: -45°~+90 Vert,360 Rotation Max fog angle : 120° Material (body) : Aluminum Material (nozzle) : Alum...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

|               |                                                                                      |
|---------------|--------------------------------------------------------------------------------------|
| Category      | Manual Operated Fire Monitor                                                         |
| Standard      | EN                                                                                   |
| Material      | -45°~+90 Vert,360 Rotation<br>Max fog angle : 120° Material<br>(body) : Aluminum ... |
| Weight / Size | -45°~+90 Vert,360 Rotation<br>Max fog angle : 120° Material<br>(body) : Aluminum ... |
| Certificate   | ABS, LR, BV, DNVGL, NK, KR,<br>IRS, RMRS, CCS                                        |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

| Technical Specifications |                                                                                                                                                                                                                                                              |             |                                                                                                                                                                                                                                                              |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Category                 | Manual Operated Fire Monitor                                                                                                                                                                                                                                 | Model / SKU | Manual-Monitor-PS30-50A                                                                                                                                                                                                                                      |
| Standard                 | EN                                                                                                                                                                                                                                                           | Material    | -45°~+90 Vert,360 Rotation Max fog angle : 120° Material (body) : Aluminum Material (nozzle) : Aluminum Material (Tiller) : 304 stainless steel with rubber handle Pump requirement for minimum performance : 30L/S@ 8 bar Pipe dimensions for installation: |
| Weight / Size            | -45°~+90 Vert,360 Rotation Max fog angle : 120° Material (body) : Aluminum Material (nozzle) : Aluminum Material (Tiller) : 304 stainless steel with rubber handle Pump requirement for minimum performance : 30L/S@ 8 bar Pipe dimensions for installation: | Certificate | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS                                                                                                                                                                                                                   |
| Warranty                 | 12 Months unless specified otherwise                                                                                                                                                                                                                         | Origin      | China                                                                                                                                                                                                                                                        |

## China Manual Monitor PS30-50A:

Type: PS30-50A  
Flow Range: 30-40-50 L/S Adjustable  
Working Pressure: 10 bar  
Max Reach @ Max Flow: 65m  
Range of motion: -45°~+90 Vert,360 Rotation  
Max fog angle : 120°  
Material (body) : Aluminum  
Material (nozzle) : Aluminum  
Material (Tiller) : 304 stainless steel with rubber handle  
Pump requirement for minimum performance : 30L/S@ 8 bar  
Pipe dimensions for installation: 4 Inch  
Monitor Inlet : DN100 flange  
Monitor Outlet : 2.5 inch (65mm)  
Paint: Fire Red  
Weight: 16KG

