

MARINE OIL WATER SEPERATOR

Marine Bilge Water Separator

China Marine Bilge Water Separator This Marine Bilge Water Separator can treat in bilge water effectively,make the oil content in effluent water≤15ppm,satisfy with the requirements of IMO MEPC.107(49). The ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Oil Water Seperator
Standard	EN
Weight / Size	Type YWC- Technical Specifications 0.25 0.5 1 1.5 2 2.5 3 4 5 Rated capa...
Certificate	CCS,GL,BV etc.
We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.	

Technical Specifications			
Category	Marine Oil Water Seperator	Model / SKU	Marine-Bilge-Water-Separator
Standard	EN	Weight / Size	Type YWC- Technical Specifications 0.25 0.5 1 1.5 2 2.5 3 4 5 Rated capacity(m3/h) 0.25 0.5 1 1.5 2 2.5 3 4 5 Oil content of the discharged water Not more than 15ppm Power of the electric heater (kw) 1kw 3kw 6 6 6 6 12 12 Electrical System AC 380V、 50Hz、 3φ/ AC 415V、 50Hz、 3φ/AC 440、 60Hz、 3φ/AC 480V、 60HZ、 3φ Power of the electric motor 0.37kw 0.55kw 0.75kw 1.1kw 1.1kw 1.5kw 1.5kw 2.2kw 2.2kw Suction head Not more than 6m-H2O Pressure of the discharged water 5-10m-H2O Outline Dimension (Length×Width×Height) (mm) 1000×600 1100×690 1050×1000 1100×1130 1900×1120 1900×1120 1700×1500 2280×1700 2590×2000 ×1250 ×1460 ×1620 ×1650 ×1700 ×1900 ×1900 ×1900 ×1900 base 5# 6# 6# 6# 8# 8# 8# 10# 10# Weight Dry Weight 400 600 800 1060 1260 1500 1800 2100 2500 Wet Weight 550 900 1200 1650 2260 2800 3200 3900 4600
Certificate	CCS,GL,BV etc.	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

■ China Marine Bilge Water Separator

■ Technical Data:

China Marine Bilge Water Separator

This Marine Bilge Water Separator can treat in bilge water effectively,make the oil content in effluent water≤15ppm,satisfy with the requirements of IMO MEPC.107(49).

The device adopts the combination of 1st stage, cone plate gravity and coalesce separation

2nd stage, fiber filter and 3rd stage, membrane permeation in order to make the treated bilge water to reach the requirements of discharge standard of the resolution of IMO MEPC.107 (49).

Technical Data:

Type		YWC-								
Technical Specifications		0.25	0.5	1	1.5	2	2.5	3	4	5
Rated capacity(m3/h)		0.25	0.5	1	1.5	2	2.5	3	4	5
Oil content of the discharged water		Not more than 15ppm								
Power of the electric heater (kw)		1kw	3kw	6	6	6	6	6	12	12
Electrical System		AC 380V、50Hz、3φ/ AC 415V、50Hz、3φ/AC 440、60Hz、3φ/AC 480V、60HZ、3φ								
Power of the electric motor		0.37kw	0.55kw	0.75kw	1.1kw	1.1kw	1.5kw	1.5kw	2.2kw	2.2kw
Suction head		Not more than 6m-H2O								
Pressure of the discharged water		5-10m-H2O								
Outline Dimension (Length×Width×Height) (mm)		1000×600	1100×690	1050×1000	1100×1130	1900×1120	1900×1120	1700×1500	2280×1700	2590×2000
		×1250	×1460	×1620	×1650	×1700	×1900	×1900	×1900	×1900
base		5#	6#	6#	6#	8#	8#	8#	10#	10#
Weight	Dry Weight	400	600	800	1060	1260	1500	1800	2100	2500
	Wet Weight	550	900	1200	1650	2260	2800	3200	3900	4600