

GB MARINE QUICK CLOSING VALVE

Marine Bronze Air-Actuated Quick Closing Valve

Marine Bronze Pneumatic Quick Closing Valve is air-actuated, and also can be controlled by the rope, used as the emergency shut-off valve for marine fresh water, fuel oil, lubrication oil pipe system. It also can be open...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	GB Marine Quick Closing Valve
Standard	GB
Material	Bronze
Weight / Size	Body-Bronze Bonnet-Bronze Disc-Bronze Stem-Stainless Steel / Brass Pisto...
Certificate	CCS, BV, DNV/GL, RINA, NK, ABS, GL,IRS, RMRS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	GB Marine Quick Closing Valve	Model / SKU	Marine-Bronze-Air-Actuated-Quick-Closing-Valve
Standard	GB	Material	Bronze
Weight / Size	Body-Bronze Bonnet-Bronze Disc-Bronze Stem-Stainless Steel / Brass Piston-Brass Air Cylinder---Stainless Steel Main Size(mm):	Certificate	CCS, BV, DNV/GL, RINA, NK, ABS, GL,IRS, RMRS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

- China Marine Bronze Air-Actuated Quick Closing Valve:
- Main Parts & Material:
- Technical Specification:
- Main Size(mm):

China Marine Bronze Air-Actuated Quick Closing Valve:



Marine Bronze Air-Actuated Quick Closing Valve

Marine Bronze Pneumatic Quick Closing Valve is air-actuated, and also can be controlled by the rope, used as the emergency shut-off valve for marine fresh water, fuel oil, lubrication oil pipe system. It also can be opened/closed by the handwheel as the stop valve. When in emergency, it can be closed by hand on the spot, or remotely.

Technical Specification:

Design Standard: GB/T5744-2008

Test Standard: GB600

Nominal Pressure: 0.6Mpa~2.5Mpa

Flange Standard: GB2501

Working Pressure of Cylinder: 0.3~0.7Mpa

Main Parts & Material:

Body-Bronze

Bonnet-Bronze

Disc-Bronze

Stem-Stainless Steel / Brass

Piston-Brass

Air Cylinder---Stainless Steel

Main Size(mm):

Nomi nal Size	Structural Size				Han dwh eel	Lift Ran ge	Flange												Cylind er Volum e	
	L		H				b	PN6			PN10			PN16			PN25			
	Type A	Type B	Type A	Type B				D	D 1	n- d	D	D 1	n- d	D	D 1	n- d	D	D 1		n- d
DN	Type A	Type B	Type A	Type B	Do	m		D	D 1	n- d	D	D 1	n- d	D	D 1	n- d	D	D 1	n- d	L

15	13 0	90	20 5	22 0	1 9 8	80	8	1 4	8 0	5 5	4- 11	9 5	6 5	4- 1 4	9 5	6 5	4- 14	9 5	6 5	4- 14	0.075
20	15 0	95	21 0	22 0	1 9 8	80	8	1 6	9 0	6 5	4- 11	1 0 5	7 5	4- 1 4	1 0 5	7 5	4- 14	1 0 5	7 5	4- 14	
25	16 0	10 0	23 0	22 0	1 9 8	80	9	1 6	1 0 0	7 5	4- 11	11 5	8 5	4- 1 4	11 5	8 5	4- 14	11 5	8 5	4- 14	
32	18 0	10 5	23 0	22 0	1 9 8	100	9	1 8	1 2 0	9 0	4- 1 4	1 4 0	1 0 0	4- 1 8	1 4 0	1 0 0	4- 18	1 4 0	1 0 0	4- 18	
40	20 0	11 5	26 0	26 5	2 3 5	120	13	1 8	1 3 0	1 0 0	4- 1 4	1 5 0	11 0	4- 1 8	1 5 0	11 0	4- 18	1 5 0	11 0	4- 18	
50	23 0	12 5	29 0	26 5	2 4 0	140	16	2 0	1 4 0	11 0	4- 1 4	1 6 5	1 2 5	4- 1 8	1 6 5	1 2 5	4- 18	1 6 5	1 2 5	4- 18	0.166
65	29 0	14 5	31 5	29 0	2 4 5	140	19	2 2	1 6 0	1 3 0	4- 1 4	1 8 5	1 4 5	8- 1 8	1 8 5	1 4 5	8- 18	1 8 5	1 4 5	8- 18	
80	31 0	15 5	33 0	30 0	2 4 5	160	23	2 2	1 9 0	1 5 0	4- 1 8	2 0 0	1 6 0	8- 1 8	2 0 0	1 6 0	8- 18	2 0 0	1 6 0	8- 18	
100	35 0	17 5	38 5	33 5	2 4 5	180	30	2 2	2 1 0	1 7 0	4- 1 8	2 2 0	2 8 0	8- 1 8	2 2 0	2 8 0	8- 18	2 3 5	1 9 0	8- 22	
125	40 0	20 0	44 2	36 5	2 5 5	180	40	2 2	2 4 0	2 0 0	8- 1 8	2 5 0	2 1 5	8- 2 2	2 5 0	2 1 5	8- 22	2 7 0	2 2 0	8- 26	
150	48 0	22 5	48 5	40 0	2 6 0	200	44	2 4	2 6 5	2 5 5	8- 1 8	2 8 5	2 4 0	8- 2 2	2 8 5	2 4 0	8- 22	3 0 0	2 5 0	8- 26	
200	60 0	27 5	60 5	51 0	2 8 0	320	64	2 4	3 2 0	2 8 0	8- 1 8	3 4 0	2 9 5	8- 2 2	3 4 0	2 9 5	12- 2 2	3 6 0	3 1 0	12- 2 6	