

JIS MARINE ANGLE VALVE

Marine Bronze Angle Valve JIS F7389 20K

ISO9001 Supplier

Class Certificate

Export Supply

Marine Bronze 20K Angle Valve JIS F7389 is a kind of ferrule type angle valve, used to connect the small size pipe, and shut off and turn on the medium in the pipeline. There are S type and U type. Technical S...



Key Highlights

Category	JIS Marine Angle Valve
Standard	JIS
Material	Bronze
Weight / Size	Marine Bronze 20K Angle Valve JIS F7389 is a kind of ferrule type angle ...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	JIS Marine Angle Valve	Model / SKU	Marine-Bronze-Angle-Valve-JIS-F7389-20K
Standard	JIS	Material	Bronze
Weight / Size	Marine Bronze 20K Angle Valve JIS F7389 is a kind of ferrule type angle valve, used to connect the small size pipe, and shut off and turn on the medium in the pipeline.	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

- China Marine Bronze Angle Valve JIS F7389 20K:
 - Main Material:
- Technical Specification:
 - Main Data for Joining(mm):

China Marine Bronze Angle Valve JIS F7389 20K:



Marine Bronze Angle Valve JIS F7389 20K

Marine Bronze 20K Angle Valve JIS F7389 is a kind of ferrule type angle valve, used to connect the small size pipe, and shut off and turn on the medium in the pipeline. There are S type and U type.

Technical Specification:

1. Design and Manufacturing Standard: JIS F7389
2. Suitable Medium: Steam, Fresh Water, Fuel Oil and Lubrication Oil
3. Hydraulic Test Pressure: Body-4.20Mpa, Seat-3.08Mpa
4. Max Working Pressure: 1.6Mpa for Steam of 205°C or less, 2.0Mpa for air, gas, oil and plusation water, 2.8Mpa for non-shock water of 120°C or less.

Main Material:

- 1-Body: Bronze (BC6)
- 2-Disc: Brass
- 3-Stem: Brass (C3771BD)

Main Data for Joining(mm):

IMPA CODE	SIZE	Pipe Outside Diameter		L1	L2	L3	K	d3	H	D2	Weight(kgs)
		Copper	Steel								
750561	6	8 & 10	10.5	32	32	41	12	M20x1.5	95	63	0.83
750562	10	15	17.3	39	35	51	16	M24x2	105	80	1.19

* When copper pipe is applied, a valve with bite type union may be used.