GB MARINE GLOBE VALVE

Marine Bronze Male Thread Globe Valve GB595-83 Type A

ISO9001 Supplier

Class Certificate

Export Supply

Marine Bronze Male Thread Globe Valve is also can be called as marine bronze male thread stop valve.There are two types, A is straight type, B is angle type. Design Standard: GB595-83 Test Standard: GB6...

Key Highlights

Category	GB Marine Globe Valve
Standard	GB
Material	Bronze
Weight / Size	Body-Bronze Bonnet-Bronze Disc-Bronze Stem-Bronze Main Size List(mm):
Certificate	CCS, BV, ABS, GL, LR, DNV, NK,RINA, KR,IRS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	GB Marine Globe Valve	**Model / SKU**	Marine-Bronze-Male-Thread-Globe-Valve-GB595-83-Type-A
Standard	GB	**Material**	Bronze
Weight / Size	Body-Bronze Bonnet-Bronze Disc-Bronze Stem-Bronze Main Size List(mm):	**Certificate**	CCS, BV, ABS, GL, LR, DNV, NK,RINA, KR,IRS
Warranty	12 Months unless specified otherwise	**Origin**	China

CONTENTS

- China Marine Bronze Male Thread Globe Valve GB595-83 Type A:
- Main Size List(mm):
- Main Material:

China Marine Bronze Male Thread Globe Valve GB595-83 Type A:

Marine Bronze Male Thread Globe Valve is also can be called as marine bronze male thread stop valve.There are two types, A is straight type, B is angle type.

Design Standard: GB595-83

Test Standard: GB600

Nominal Pressure (Mpa)	Nominal diameter(mm)	Applicable medium
4.0	15--32	fresh water, lubrication oil, fuel oil, steam not over 250℃
10.0	6--32	

Main Material:

Body-Bronze

Bonnet-Bronze

Disc-Bronze

Stem-Bronze

Main Size List(mm):

DN6--DN10

PN (MPa)	DN (mm)	Structure Dimension					thread joint					wrench size	hand wheel		lift range m	Weight(kg)	
		L		H≈	H1												
		Type A	Type B		Type A	Type B	D	D1	D2	l	l1	S2	D0	S1		Type A	Type B
10.0	6	74	37	90	12	32	M22×1.5	19.8	10	14	3	24	65	7	5	0.48	0.45
	10	94	47	109	16	38	M27×1.5	24.8	14	16	3	30	80	8	7	0.87	0.85

DN15--DN32

PN (MPa)	DN (mm)	Structure Dimension					thread joint					wrench size S2		hand wheel		lift range m	Weight(kg)	
		L		H≈	H1													
		Type A	Type B		Type A	Type B	D	D1	D2	l	l1	Type A	Type B	D0	S1		Type A	Type B

4.0	15	110	55	143	25	52	M36×2	33	22	22	5	32	41	80	8	10	1.51	1.45
	20	116	58	153	32	55	M39×2	36	25	23	5	36	46	100	9	12	1.81	1.77
	25	130	65	167	38	64	M48×2	45	32	26	6	46	50	120	11	14	2.54	2.60
	32	140	70	197	46	72	M56×2	53	38	28	6	46	60	140	12	16	4.31	4.08
10.0	15	120	60	164	27	52	M36×2	33	22	22	5	32	41	120	11	10	2.10	1.96
	20	134	67	194	32	55	M39×2	36	25	23	5	36	46	140	12	12	3.06	2.88
	25	134	67	204	38	64	M48×2	45	32	26	6	46	55	140	12	14	3.61	3.49
	32	146	73	220	46	75	M56×2	53	38	28	6	55	65	160	14	16	4.99	4.25