Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

GB MARINE GLOBE VALVE

Marine Bronze Male Thread Globe Valve GB595-83 Type A

ISO9001 Supplier

Class Certificate

Export Supply

Marine Bronze Male Thread Globe Valve is also can be called as marine bronze male thread stop valve.There are two types, A is straight type, B is angle type. Design Standard: GB595-83 Test Standard: GB6...

Key Highlights

Category	GB Marine Globe Valve
Standard	GB
Material	Bronze
Weight / Size	Body-Bronze Bonnet-Bronze Disc-Bronze Stem-Bronze Main Size List(mm):
Certificate	CCS, BV, ABS, GL, LR, DNV, NK,RINA, KR,IRS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	GB Marine Globe Valve	Model / SKU	Marine-Bronze-Male-Thread-Globe-Valve-GB595-83-Type-A
Standard	GB	Material	Bronze
Weight / Size	Body-Bronze Bonnet-Bronze Disc-Bronze Stem-Bronze Main Size List(mm):	Certificate	CCS, BV, ABS, GL, LR, DNV, NK,RINA, KR,IRS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

- China Marine Bronze Male Thread Globe Valve GB595-83 Type A:
- Main Size List(mm):
- Main Material:

China Marine Bronze Male Thread Globe Valve GB595-83 Type A:

Marine Bronze Male Thread Globe Valve is also can be called as marine bronze male thread stop valve.There are two types, A is straight type, B is angle type.

Design Standard: GB595-83

Test Standard: GB600

Nominal Pressure (Mpa)	Nominal diameter(mm)	Applicable medium
4.0	15--32	fresh water, lubrication oil, fuel oil, steam not over 250℃
10.0	6--32	

Main Material:

Body-Bronze

Bonnet-Bronze

Disc-Bronze

Stem-Bronze

Main Size List(mm):

DN6--DN10

PN (MPa)	DN (mm)	Structure Dimension					thread joint					wrench size	hand wheel		lift range m	Weight(kg)	
		L		H≈	H1												
		Type A	Type B		Type A	Type B	D	D1	D2	I	I1	S2	D0	S1		Type A	Type B
10.0	6	74	37	90	12	32	M22×1.5	19.8	10	14	3	24	65	7	5	0.48	0.45
	10	94	47	109	16	38	M27×1.5	24.8	14	16	3	30	80	8	7	0.87	0.85

DN15--DN32

PN (MPa)	DN (mm)	Structure Dimension					thread joint					wrench size S2		hand wheel		lift range m	Weight(kg)	
		L		H≈	H1													
		Type A	Type B		Type A	Type B	D	D1	D2	I	I1	Type A	Type B	D0	S1		Type A	Type B

4.0	15	110	55	143	25	52	M36×2	33	22	22	5	32	41	80	8	10	1.51	1.45
	20	116	58	153	32	55	M39×2	36	25	23	5	36	46	100	9	12	1.81	1.77
	25	130	65	167	38	64	M48×2	45	32	26	6	46	50	120	11	14	2.54	2.60
	32	140	70	197	46	72	M56×2	53	38	28	6	46	60	140	12	16	4.31	4.08
10.0	15	120	60	164	27	52	M36×2	33	22	22	5	32	41	120	11	10	2.10	1.96
	20	134	67	194	32	55	M39×2	36	25	23	5	36	46	140	12	12	3.06	2.88
	25	134	67	204	38	64	M48×2	45	32	26	6	46	55	140	12	14	3.61	3.49
	32	146	73	220	46	75	M56×2	53	38	28	6	55	65	160	14	16	4.99	4.25