

JIS MARINE STRAINER & FILTER

Marine Cast Iron Y strainer JIS F7220 5K

ISO9001 Supplier

Class Certificate

Export Supply

Y Strainer is normally installed in the inlet side of the hydraulic control valve,relief valve, relief valve, inlet pressure water valves and other equipments, used to remove the impurities in the medium in order to...



Key Highlights

Category	JIS Marine Strainer & Filter
Standard	JIS
Material	cast iron
Weight / Size	Body- 1.05Mpa Flange size as per JIS B2220 - 5K Marine Material:
Certificate	Mill Certificate

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	JIS Marine Strainer & Filter	Model / SKU	Marine-Cast-Iron-Y-strainer-JIS-F7220-5K
Standard	JIS	Material	cast iron
Weight / Size	Body- 1.05Mpa Flange size as per JIS B2220 - 5K Marine Material:	Certificate	Mill Certificate
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

- China Marine Cast Iron Y strainer JIS F7220 5K:
- Marine Material:
- Main Size List(mm):

China Marine Cast Iron Y strainer JIS F7220 5K:

Y Strainer is normally installed in the inlet side of the hydraulic control valve, relief valve, inlet pressure water valves and other equipments, used to remove the impurities in the medium in order to protect the equipment and pipe fittings.

Design Standard: JIS F7220-1996

Test Standard: JIS 7200-1996

Hydraulic Test Pressure: Body- 1.05Mpa

Flange size as per JIS B2220 - 5K

Marine Material:

- 1.Body-Cast Iron (FC200)
- 2.Bonnet-Cast Iron (FC200)
- 3.Strainer-Stainless Steel (SUS304)
- 4.Gasket:non-asbestos

Main Size List(mm):

DN	d	L	D	C	Hole (n-d)	t	H
20	20	200	85	65	4-12	14	127
25	25	225	95	75	4-12	14	155
32	32	260	115	90	4-15	16	164
40	40	280	120	95	4-15	16	180
50	50	320	130	105	4-15	16	208
65	65	350	155	130	4-15	18	253
80	80	373	180	145	4-19	18	268
100	100	390	200	165	8-19	20	286
125	125	410	235	200	8-19	20	295
150	150	430	265	230	8-19	20	318