

OIL HOSE

Marine Dock Oil Hose With Steel Flange

ISO9001 Supplier

Class Certificate

Export Supply

T: Black Butanenitrile/Neoprene Rubber C: Black Butanenitrile/Neoprene Rubber R: Multi-layer fiber layer with spiral wire strengthening Temperature: -30°Cto +80°C Safety Factor: 1:3 Spe...



Key Highlights

Category	Oil Hose
Standard	EN
Material	Black Butanenitrile/Neoprene Rubber
Weight / Size	1:3 Specification ID OD Length Bend radium WP Weight in mm in mm ft m in...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Oil Hose	Model / SKU	Marine-Dock-Oil-Hose-With-Steel-Flange
Standard	EN	Material	Black Butanenitrile/Neoprene Rubber
Weight / Size	1:3 Specification ID OD Length Bend radius WP Weight in mm in mm ft m in mm Psi Kg/cm² Kg/m 2 50.8 2.575 65.4 66-133 20-40 12 300 225 15 1.84 2 1/2 63.5 3.217 81.7 66-133 20-40 16 400 225 15 2.8 3 76.2 3.764 95.6 66-133 20-40 18 450 225 15 3.48 4 101.6 4.803 122 66-133 20-40 24 600 225 15 4.74 5 127 5.945 151 66-133 20-40 30 750 225 15 6.85 6 152.4 6.976 177.2 66-133 20-40 36 900 225 15 8.33 8 203.2 9.197 233.6 66-133 20-40 48 1200 225 15 13.51 10 254 11.433 290.4 33-100 10-30 60 1500 225 15 19.31 12 304.8 13.638 346.4 33-100 10-30 72 1800 225 15 26.36	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS	■ China Marine Dock Oil Hose With Steel Flange:	■ Specification
----------	---	-----------------

China Marine Dock Oil Hose With Steel Flange:

- T: Black Butanenitrile/Neoprene Rubber
- C: Black Butanenitrile/Neoprene Rubber
- R: Multi-layer fiber layer with spiral wire strengthening
- Temperature: -30°Cto +80°C
- Safety Factor: 1:3

Specification

ID		OD		Length		Bend radius		WP		Weight
in	mm	in	mm	ft	m	in	mm	Psi	Kg/cm²	Kg/m
2	50.8	2.575	65.4	66-133	20-40	12	300	225	15	1.84
2 1/2	63.5	3.217	81.7	66-133	20-40	16	400	225	15	2.8

3	76.2	3.764	95.6	66-133	20-40	18	450	225	15	3.48
4	101.6	4.803	122	66-133	20-40	24	600	225	15	4.74
5	127	5.945	151	66-133	20-40	30	750	225	15	6.85
6	152.4	6.976	177.2	66-133	20-40	36	900	225	15	8.33
8	203.2	9.197	233.6	66-133	20-40	48	1200	225	15	13.51
10	254	11.433	290.4	33-100	10-30	60	1500	225	15	19.31
12	304.8	13.638	346.4	33-100	10-30	72	1800	225	15	26.36