

WATER TREATMENT EQUIPMENT

Marine Seawater Desalinator

Marine Seawater Desalinator has wide range capacity from 0.5Ton to 100Ton water per day, easy use and safety, it can install in the cabin, deck, crew room and marine gangway.

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

|               |                                            |
|---------------|--------------------------------------------|
| Category      | Water Treatment Equipment                  |
| Standard      | EN                                         |
| Weight / Size | from 0.5Ton to 100Ton                      |
| Certificate   | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

|             |                                            |               |                                      |
|-------------|--------------------------------------------|---------------|--------------------------------------|
| Category    | Water Treatment Equipment                  | Model / SKU   | Marine-Seawater-Desalinator          |
| Standard    | EN                                         | Weight / Size | from 0.5Ton to 100Ton                |
| Certificate | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS | Warranty      | 12 Months unless specified otherwise |
| Origin      | China                                      |               |                                      |

CONTENTS

■ China Marine Seawater Desalinator:

■ Main Specification:

## China Marine Seawater Desalinator:



Marine Seawater Desalinator has wide range capacity from 0.5Ton to 100Ton water per day, easy use and safety, it can install in the cabin, deck, crew room and marine gangway.

## Main Specification:

| Model   | Output Capacity | Operational Pressure(Mpa) |                 | Power | Size           |
|---------|-----------------|---------------------------|-----------------|-------|----------------|
|         | (m3/d)          | Pretreat Ment             | Membrane System | (kw)  | ( mm)          |
| FSHB1   | 1-1.5           | 0.1-0.3                   | 4-6.5           | 2.05  | 940x440x1600   |
| FSHB2   | 2-2.5           | 0.1-0.3                   | 4-6.5           | 2.05  | 940x440x1601   |
| FSHB3   | 3-4             | 0.1-0.3                   | 4-6.5           | 2.05  | 940x440x1602   |
| FSHB5   | 5-6             | 0.1-0.3                   | 4-6.5           | 2.75  | 940x440x1603   |
| FSHB10  | 10              | 0.1-0.3                   | 4-6.5           | 6.3   | 1350x650x1800  |
| FSHB15  | 15              | 0.1-0.3                   | 4-6.5           | 6.3   | 1350x650x1801  |
| FSHB20  | 20              | 0.1-0.3                   | 4-6.5           | 8.3   | 1700x1100x1800 |
| FSHB50  | 50-60           | 0.1-0.3                   | 4-6.5           | 22    | 3000x2000x2100 |
| FSHB100 | 100-120         | 0.1-0.3                   | 4-6.5           | 40    | 3710x1300x2000 |