MARINE DOOR

Marine Steel Quick Acting Weathertight Door with Single Lever

ISO9001 Supplier

Class Certificate

Export Supply

Standard:GB/T3477-1996 for reference The steel weathertight door must pass the hose test with nozzle diameter 12.5mm and the water pressure 0.25Mpa. Type: JA-Steel weathertight door JB-Stee...



Key Highlights

Category	Marine Door
Standard	GB
Material	Steel
Weight / Size	Door Leaf-Steel (Q235A) Door Frame-Steel (Q235A) Lever-Carbon Steel or S...
Certificate	CCS, BV, ABS, GL, LR, DNV, NK,RINA, KR,IRS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.


Technical Specifications

Category	Marine Door	**Model / SKU**	Marine-Steel-Quick-Acting-Weathertight-Door-with-Single-Lever
Standard	GB	**Material**	Steel
Weight / Size	Door Leaf-Steel (Q235A) Door Frame-Steel (Q235A) Lever-Carbon Steel or Stainless Steel Main Size List(mm):	**Certificate**	CCS, BV, ABS, GL, LR, DNV, NK,RINA, KR,IRS
Warranty	12 Months unless specified otherwise	**Origin**	China

CONTENTS

- China Marine Steel Quick Acting Weathertight Door with Single Lever:
- Type:
- Main Material:
- Main Size List(mm):

China Marine Steel Quick Acting Weathertight Door with Single Lever:



Standard:GB/T3477-1996 for reference

The steel weathertight door must pass the hose test with nozzle diameter 12.5mm and the water pressure 0.25Mpa.

Type:

JA-Steel weathertight door

JB-Steel weathertight door with round window

JC-Steel weathertight door with round window & guard bar

JD-Steel weathertight door with square window

JE-Steel weathertight door with round window & deadlight

Main Material:

Door Leaf-Steel (Q235A)

Door Frame-Steel (Q235A)

Lever-Carbon Steel or Stainless Steel

Main Size List(mm):

Clear Size	Cut Out Size		Door leaf Size		Door Frame	
WXh	W1Xh1	R	W2Xh2	t	Spec	Thickness

500x1000	560x1060	130	555x1055	6,8	75x50	6,8
600x1200	660x1260		655x1255			
600x1400	660x1460		655x1455			
750x1400	810x1460		805x1455			
900x1400	960x1460		955x1455			
600x1600	660x1660		655x1655			
750x1600	810x1660		805x1655			
900x1600	960x1660		955x1655			