

TANK WASHING MACHINE

Marine Tank Cleaning Machine

YQJ B(Q)-50: weight:6.7kg operating temperature:from ordinary to 80 centigrade. YQJ B(Q)-60: weight:8.3kg operating temperature:from ordinary to 80 centigrade. Note: The dynamic ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

|               |                                                                    |
|---------------|--------------------------------------------------------------------|
| Category      | Tank Washing Machine                                               |
| Standard      | DIN                                                                |
| Material      | Antistatic rubber hose. Copper alloy or stainless steel.           |
| Weight / Size | weight:6.7kg operating temperature:from ordinary to 80 centigrade. |
| Certificate   | CCS                                                                |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

|               |                                                                    |             |                                                          |
|---------------|--------------------------------------------------------------------|-------------|----------------------------------------------------------|
| Category      | Tank Washing Machine                                               | Model / SKU | Marine-Tank-Cleaning-Machine                             |
| Standard      | DIN                                                                | Material    | Antistatic rubber hose. Copper alloy or stainless steel. |
| Weight / Size | weight:6.7kg operating temperature:from ordinary to 80 centigrade. | Certificate | CCS                                                      |
| Warranty      | 12 Months unless specified otherwise                               | Origin      | China                                                    |

CONTENTS

- YQJ B(Q)-50:  
■ Note:
- YQJ B(Q)-60:  
■ Specification:

YQJ B(Q)-50:

weight:6.7kg

operating temperature:from ordinary to 80 centigrade.

## YQJ B(Q)-60:

weight:8.3kg

operating temperature:from ordinary to 80 centigrade.

## Note:

The dynamic pressure refers to the impact pressure made by water column when striking the pressure block continuously.

Tje effective range refers to the water shot range of the washing machine when the dynamic pressure of the water column is equal or greater than 7 KPa.

## Specification:

| Model        | Nozzle (mm) | Working Pressure | Flow ( m³/h ) |           | Range |           |
|--------------|-------------|------------------|---------------|-----------|-------|-----------|
|              |             |                  | Rated         | Deviation | Rated | Deviation |
| YQJ7B(Q)-50  | 7           | 0.8              | 12            | ±5%       | 10.5  | 0-10%     |
|              |             | 0.7              | 11            |           | 9.5   |           |
|              |             | 0.6              | 10            |           | 8.5   |           |
| YQJ8B(Q)-50  | 8           | 0.8              | 13            | ±5%       | 12    | 0-10%     |
|              |             | 0.7              | 12            |           | 11    |           |
|              |             | 0.6              | 11            |           | 10    |           |
| YQJ9B(Q)-50  | 9           | 0.8              | 14            | ±5%       | 13    | 0-10%     |
|              |             | 0.7              | 13            |           | 12    |           |
|              |             | 0.6              | 12            |           | 11    |           |
| YQJ10B(Q)-50 | 10          | 0.8              | 16            | ±5%       | 14    | 0-10%     |
|              |             | 0.7              | 15            |           | 13    |           |
|              |             | 0.6              | 14            |           | 12    |           |
| YQJ11B(Q)-60 | 11          | 0.8              | 26            | ±5%       | 15    | 0-10%     |
|              |             | 0.7              | 24            |           | 13    |           |
|              |             | 0.6              | 21            |           | 12    |           |

|              |    |     |    |     |    |       |
|--------------|----|-----|----|-----|----|-------|
| YQJ12B(Q)-60 | 12 | 0.8 | 29 | ±5% | 16 | 0-10% |
|              |    | 0.7 | 27 |     | 14 |       |
|              |    | 0.6 | 24 |     | 13 |       |
| YQJ13B(Q)-60 | 13 | 0.8 | 33 | ±5% | 18 | 0-10% |
|              |    | 0.7 | 30 |     | 16 |       |
|              |    | 0.6 | 27 |     | 15 |       |
| YQJ14B(Q)-60 | 14 | 0.8 | 36 | ±5% | 20 | 0-10% |
|              |    | 0.7 | 33 |     | 18 |       |
|              |    | 0.6 | 30 |     | 16 |       |