

MARINE OIL WATER SEPERATOR

Marine YSZ-5.0 15ppm Big Oily Water Separator

ISO9001 Supplier

Class Certificate

Export Supply

Marine YSZ-5.0 15ppm Big Oily Water Separator
Model Parameter YSZ-0.1 YSZ-0.25
YSZ-...



Key Highlights

Category	Marine Oil Water Seperator
Standard	Marine YSZ-5.0 15ppm Big Oily Water Separator Model Parameter Y...
Weight / Size	Control mode Automatic Oil-discharge mode Automatic/Manual (kg) ...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Oil Water Separator	Model / SKU	Marine-YSZ-5-0-15ppm-Big-Oily-Water-Separator
Standard	Marine YSZ-5.0 15ppm Big Oily Water Separator Model Parameter YSZ-0.1 YSZ-0.25 YSZ-0.5 YSZ-1 YSZ-1.5 YSZ-2 YSZ-3 YSZ-4 YSZ-5 (m³/h) Capacity 0.1 0.25 0.5 1.0 1.5 2.0 3.0 4.0 5.0 Discharging standard ≤15ppm(IMO)MEPC.107(49) ≤15ppm satisfy(IMO)MEPC.107(49) Working pressure ≤0.3MPa Plunger pump Model DZ-100 DZ-250 DZ-500 DZ-1000 DZ-1500 DZ-2000 DZ-3000 DZ-4000 DZ-5000 (m3/h) Capacity 0.1 0.25 0.5 1.0 1.5 2.0 3.0 4.0 5.0 (MPa) Discharging pressure 0.3 (m) Suction lift 6 (kw) Motor power 0.12 0.18 0.25 0.37 0.75 0.75 1.1 1.5 1.5 (kw) Electricheating power - 1 2 2~3 3~5 Power supply 3Ph/380V/50Hz;& 3Ph/440V/60Hz;	Weight / Size	Control mode Automatic Oil-discharge mode Automatic/Manual (kg) Weight 205 350 490 600 860 890 1100 1950 2310
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

Marine YSZ-5.0 15ppm Big Oily Water Separator

Model Parameter	YSZ-0.1	YSZ-0.25	YSZ-0.5	YSZ-1	YSZ-1.5	YSZ-2	YSZ-3	YSZ-4	YSZ-5
(m³/h) Capacity	0.1	0.25	0.5	1.0	1.5	2.0	3.0	4.0	5.0
Discharging standard	≤15ppm(IMO)MEPC.107(49) ≤15ppm satisfy(IMO)MEPC.107(49)								
Working pressure	≤0.3MPa								

Plunger pump	Model	DZ-100	DZ-250	DZ-500	DZ-1000	DZ-1500	DZ-2000	DZ-3000	DZ-4000	DZ-5000
	(m3/h) Capacity	0.1	0.25	0.5	1.0	1.5	2.0	3.0	4.0	5.0
	(MPa) Discharging pressure	0.3								
	(m) Suction lift	6								
	(kw) Motor power	0.12	0.18	0.25	0.37	0.75	0.75	1.1	1.5	1.5
(kw) Electricheating power		-	1		2			2~3		3~5
Power supply		3Ph/380V/50Hz;& 3Ph/440V/60Hz;								
Control mode		Automatic								
Oil-discharge mode		Automatic/Manual								
(kg) Weight		205	350	490	600	860	890	1100	1950	2310